



### Main

Range	Kaedra
Product or component type	Weatherproof enclosure
Enclosure type	Versatile enclosure
Mounting plate description	Slotted

### Complementary

Enclosure mounting	Surface
Electrical insulation class	Double insulation Class II
Type of front cover	Opaque
Number of pre-cutouts PG ISO	17
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	340 mm
Height	460 mm
Depth	160 mm
Internal depth	130 mm
Colour	Enclosure: light grey (RAL 7035)

### Environment

Standards	EN 50102 IEC 60529 IEC 670 EN 50262 IEC 60439-3 IEC 60695-2-1
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

### Packing Units

Package 1 Weight	2.687 kg
Package 1 Height	4.700 dm
Package 1 width	3.600 dm
Package 1 Length	1.680 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------