



Main

| | |
|-----------------------------|----------------------|
| Range of product | Mureva Styl |
| Product or component type | Socket-outlet |
| Device presentation | Complete product |
| Outlet poles configuration | 2P + E with shutters |
| Outlet standard description | Side earth |
| Outlet standard | Schuko |
| Colour tint | Grey (RAL 7016) |

Complementary

| | |
|--|---|
| Device mounting | Surface |
| Rated current | 16 A |
| Number of power socket outlets | 2 |
| [Ue] rated operational voltage | 250 V AC |
| Condition of use | Indoor/outdoor |
| Material | Brass PC (polycarbonate) PP (polypropylene) |
| Fixing mode | By screws |
| Clamping connection capacity | 1...2.5 mm ² for rigid cable(s) 1...2.5 mm ² for stranded cable(s) 1...2.5 mm ² for flexible cable(s) |
| Wire stripping length | 13 mm |
| Cable entry | Easy valve access diameter: 6...12 mm |
| Height | 76 mm |
| Width | 147 mm |
| Depth | 64 mm |
| Chemical and detergent products resistance | Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane |

Environment

| | |
|---------------------------------------|---|
| Quality labels | AENOR EAC |
| IP degree of protection | IP55 |
| IK degree of protection | IK08 |
| Flame retardance | Self-extinguishing 650 °C conforming to IEC 60695-2-1 |
| Ambient air temperature for operation | -5...40 °C |
| Ambient air temperature for storage | -25...55 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |