
SDN3000168

Sedna - single socket outlet, side earth - 16A shutters, without frame titanium



Main	
Range name	Sedna
Function	Socket-outlet
Delivery form	Without frame
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Outlet standard	Poland
Rated current	16 A at 250 V AC

Complementary

Complementary		
Power range	3680 W	
Kind of terminals	Lift terminals	
Terminal capacity	2 cable(s) 2.5 mm ²	
Wire structure	Rigid Flexible	
Wire stripping length	13 mm	
Material of visible parts	PC	
Surface finish	Glossy	
Fixing mode	Claws, span of claws working range: 5269 mm Screws	
Height	71 mm	
Width	71 mm	
Depth	41.3 mm	
Depth of visual part	10 mm	
Net weight	0.067822 kg	

Environment

Standards	IEC 60884-1
Product certifications	GOST-R
IP degree of protection	IP20

Packing Units

1 doking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	69 g
Package 1 Height	4.1 cm
Package 1 width	7.1 cm
Package 1 Length	7.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	773.33 g
Package 2 Height	9.5 cm
Package 2 width	18.5 cm
Package 2 Length	27.5 cm
Unit Type of Package 3	S04

Number of Units in Package 3	120
Package 3 Weight	9.955 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

EU RoHS Directive	Compliant EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Wallanty	Warranty	18 months
----------	----------	-----------