



Main

Range	Unica
Product or component type	Trailing lead
Aesthetic name	Unica extend
Shape	Square
Control type	Mains switch
Socket number	5
Number of power socket outlets	5 square
Cable length	3 m
Colour tint	White

Complementary

Number of socket outlets with earth pin	5
[Ue] rated operational voltage	250 V
Number of USB connection	0
[In] rated current	16 A
On/off switch present	True
Outlet poles configuration	2P + E
Outlet standard	Schuko
Socket additional information	Shuttered
Maximum switching capacity	16 A
Pilot light	ON indicator
Material	PP (polypropylene)
Length	290.5 mm
Width	57 mm
Depth	40.5 mm
Quantity per set	Set of 1
Type of packing	Film
Colour	White
Surface treatment	Untreated

Packing Units

Package 1 Weight	595.000 g
Package 1 Height	80.000 mm
Package 1 width	65.000 mm
Package 1 Length	345.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
