



Main

Range of product	Thorsman
Product or component type	Wall plug
Device short name	TP
Provided equipment	Without screw
Drilling diameter	12 Mm concrete 10 mm ALC concrete
Minimum drilling depth	65 mm
Screw diameter	8...10 mm
Material	PEHD (polyethylene high density)

Complementary

Practical load capacity	Shear: 3 kN for concrete C25 4.5) Pull-out load: 2 kN for concrete C25 6) Shear: 0.5 kN for low density concrete 500 and expanded clay 4.5) Pull-out load: 0.25 kN for low density concrete 500 and expanded clay 6)
Practical load capacity	Shear: 50 kg for solid brick 4.5) Pull-out load: 25 kg for solid brick 6) Shear: 300 kg for concrete C25 4.5) Pull-out load: 200 kg for concrete C25 6)
Colour tint	Green
Ambient air temperature for operation	-50...80 °C
Diameter	12 mm
Length	60 mm

Environment

Quantity per set	Set of 50
Sale per indivisible quantity	10

Packing Units

Package 1 Weight	5.000 g
Package 1 Height	87.000 mm
Package 1 width	132.000 mm
Package 1 Length	94.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile