



### Main

Range	Altira
Product or component type	Socket-outlet
Range compatibility	Fixing frame Fixing frame
Device presentation	Mechanism
Number of power socket outlets	2 x 2P + E, German
Outlet standard description	Side earth
Socket additional information	Shuttered
Colour tint	Cover plate: red (RAL 3000)

### Complementary

Product destination	Fixing frames
Range compatibility	OptiLine 70 with Altira adaptor OptiLine 45
Ground lug position	Slanted 45° position
Rated current	16 A at 250 V AC 50/60 Hz
Number of modules	4 modules
Fixing mode	Clip-in
Connections - terminals	Screwless terminals
Clamping connection capacity	4 x 1.5...4 x 2.5 mm <sup>2</sup> for rigid cable(s) 4 x 1.5...4 x 2.5 mm <sup>2</sup> for solid stranded cable(s)
Material	PC: mechanism cover
Surface treatment	Antibacterial
Surface finish	Satin
Standards	EN 62262 NF C 61-314 IEC 60884-1 EN 60529
Height	45 mm
Width	90 mm
Depth	39 mm
Net weight	0.087 kg

### Environment

Ambient air temperature for operation	5...50 °C
Ambient air temperature for storage	-15...60 °C
IK degree of protection	IK02
IP degree of protection	IP20
Environmental characteristic	Hydrogen peroxide (H2O2) Oil Bleach Liquid soap Petrol Alcohol Acetone UV resistant Window-cleaning fluid Ammonia

## Packing Units

Package 1 Weight	0.082 kg
Package 1 Height	0.400 dm
Package 1 width	0.900 dm
Package 1 Length	0.400 dm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------