



### Main

Range	Asfora
Product or component type	Socket-outlet
Outlet poles configuration	2P
Device presentation	Complete product
Colour tint	White
Type of packing	Flow-pack

### Complementary

Socket number	1
Device mounting	Flush
Power range	3680 W
Rated current	16 A at 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 cable(s) 2.5 mm <sup>2</sup>
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13.0 mm
Material	ABS (acrylonitrile butadiene-styrene): cover frame ABS + PC: central plate
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws 51...69 mm
Height	83 mm
Width	83 mm
Depth	42 mm
Projecting depth	10 mm
Quantity per set	1
Net weight	0.072 kg

### Environment

Standards	IEC 60884-1
Product certifications	SEP-BBJ TSE
IP degree of protection	IP20

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins