ST945U1WA

Unica extend - Schuko trailing lead - 5 gangs - with USB port - aluminium/white





Main

| Range | Unica |
|--------------------------------|--|
| Product or component type | Trailing lead |
| Aesthetic name | Unica extend |
| Shape | Square |
| Control type | Mains switch |
| Socket number | 5 |
| Number of power socket outlets | 5 square |
| Integrated connection type | 2 USB port 5 V DC, maximum load current: 2.4 A |
| Cable length | 1.5 m |
| Colour tint | Aluminium/white |

Complementary

| Number of socket outlets with earth pin | 5 |
|---|--------------------------|
| [Ue] rated operational voltage | 250 V |
| Number of USB connection | 2 |
| [In] rated current | 16 A |
| On/off switch present | True |
| Outlet poles configuration | 2P + E |
| Outlet standard | Schuko |
| Socket additional information | Shuttered |
| Maximum switching capacity | 16 A |
| Pilot light | ON indicator |
| Material | PC PP (polypropylene) |
| Length | 339 mm |
| Width | 57 mm |
| Depth | 40.5 mm |
| Quantity per set | Set of 1 |
| Type of packing | Blister |
| Colour | Aluminium/white |
| Surface treatment | Untreated |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|---------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Weight | 601 g | |
| Package 1 Height | 4.5 cm | |
| Package 1 width | 13.6 cm | |
| Package 1 Length | 41.5 cm | |
| | | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|---|
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | ₫Yes |
| China RoHS Regulation | ☑ China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | ☑ End Of Life Information |