



 PRODUCT-DETAILS

TAC-W11-S-R-0

TAC-W11-S-R-0 Terra AC wallbox type 2, socket with shutter, 3-phase/16 A, with RFID



General Information

Extended Product Type	TAC-W11-S-R-0
Product ID	6AGC105907
EAN	8719874452878
Alternative Product Reference	3Q510001922A
Catalog Description	TAC-W11-S-R-0 Terra AC wallbox type 2, socket with shutter, 3-phase/16 A, with RFID
Long Description	Terra AC wallbox type 2, socket with shutter, 3-phase/16 A, with RFID

Technical

Overload Protection	Overcurrent protection at 20 A
Communication Interface	Wi-Fi Ethernet Bluetooth Modbus
Number of Phases	3-phase
Number of Miniature Circuit Breakers (MCBs)	Integrated breaker
Surge Suppression	Included
Energy Meter Type	AC

Screen Type	No display
Technical Information	Features: DC residual current detection Contactor welding detection Networkable via LAN Networkable via Wi-Fi Long-Term Evolution (LTE) Static load management integrated Suitable for dynamic load management With Display Operation and configuration by app Export of charging logs Backend included in delivery
Number of Batteries	1
Battery Chemical Composition	Lithium
Battery Weight	0.8 g
EV Connectors	No cable outlet
Number of Socket Outlets	(AC Type 2 with Shutter) 1 piece
Output Power	Nominal 11 kW
Connection Power	Nominal 11 kW
Input Current	3-phase 16 A
Number of RCDs Electric Vehicle Supply Equipment	Resid. Curr. Monitor
Cross-Section (A_{CROSS})	6 ... 6 mm ²
Communication Protocol	OCPP 1.6
Load Management Method	OCPP - Based
Authentication Method	RFID App Free Vending
Impact Resistance Rating	IK08

Electrical

Input Voltage (U_{in})	AC 3-phase 380 ... 420 V
Output Voltage (U_{out})	AC 3-phase 320 ... 480 V
Output Current Maximum (I_{out})	AC 3-phase 16 A
Frequency (f)	50 ... 60 Hz
Overvoltage Category	III

Design

Housing Material	Plastic
------------------	---------

Material Compliance

REACH Declaration	9AKK108467A5693
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20210928
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B	Business To Business
Battery Type	Button Cell

Environmental

Degree of Protection	acc. to IEC 60529 IP54
Maximum Operating Altitude Permissible	2000 m

Dimensions

Product Net Width	195 mm
Product Net Height	110 mm
Product Net Depth / Length	320 mm
Product Net Weight	2.7 kg

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	3.5 kg
E-Number (Finland)	3503462
Alternative Product Reference	3Q510001922A

Certificates and Declarations

Declaration of Conformity - CE	9AKK108467A2511
--------------------------------	-----------------

Installation

Mounting Type	Wall mounting
---------------	---------------

External Classifications and Standards

ETIM 9	EC002883 - Charging device E-Mobility
ETIM 10	EC002883 - Charging device for electric vehicles
UNSPSC	25175002
IDEA Granular Category Code (IGCC)	1311 >> Electric vehicle charging station
Standards	EN 61851-1 EN 61851-23 EN 61000-6-2 EN 61000-6-3 EN 301 908-2 IEC 60721-3-2: IE23 RoHS

Categories

Electric Vehicle Charging → Home Charging Products, AC and DC Wallboxes and Chargers → Global AC Chargers

