



PRODUCT-DETAILS

OTC125G3-4BS

OTC125G3-4BS CHANGE-OVER SWITCH



General Information	
Extended Product Type:	OTC125G3-4BS
Product ID:	1SCA162750R1001
EAN:	6417019928180
Catalog Description:	OTC125G3-4BS CHANGE-OVER SWITCH
Long Description:	OT Plus Switch disconnecter series. 4-pole front operated base mounted DIN-rail mountable change-over switch. The change-over switch has inbuilt screw terminals and comes with direct-mounted knob handle that can be padlocked and shaft can be mounted for external operation.
Display Name:	OTC125G3-4BS

Material Compliance	
Conflict Minerals Reporting Template (CMRT):	9AKK108467A5658
REACH Declaration:	1SCC011021D0201
RoHS Declaration:	1SCC011020D0201
RoHS Information:	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA:	1SCC011025D0201

Environmental

Degree of Protection:	Front IP20
-----------------------	------------

Pollution Degree:	3
-------------------	---

Ordering

Minimum Order Quantity:	1 piece
-------------------------	---------

Customs Tariff Number:	85365080
------------------------	----------

Country of Origin:	Finland
--------------------	---------

Dimensions

Product Net Width:	123 mm
--------------------	--------

Product Net Height:	191 mm
---------------------	--------

Product Net Depth / Length:	95 mm
-----------------------------	-------

Product Net Weight:	1.100 kg
---------------------	----------

Container Information

Package Level 1 Units:	box 1 piece
------------------------	-------------

Package Level 1 Width:	102 mm
------------------------	--------

Package Level 1 Depth / Length:	195 mm
---------------------------------	--------

Package Level 1 Height:	127 mm
-------------------------	--------

Package Level 1 EAN:	6417019928180
----------------------	---------------

Technical

Connecting Capacity Main Circuit:	Flexible with Ferrule 1/2x Cu 2.5...4 mm ² Solid 1/2x Cu 2.5...6 mm ² Flexible 1x Cu 2.5...70 mm ² Flexible 2x Cu 2.5...25 mm ² Stranded 1x Cu 2.5...70 mm ² Stranded 2x Cu 2.5...25 mm ²
-----------------------------------	--

Conventional Free-air Thermal Current (I _{th}):	125 A
---	-------

Conventional Thermal Current (I _{the}):	125 A
---	-------

Fourth Pole Position:	Right Side Left Side
-----------------------	-------------------------

Fourth Pole Type:	Switched - Simultaneous Function Switched - Late-break and Early-make
-------------------	--

Handle Color:	Black
---------------	-------

Handle Length:	57 mm
----------------	-------

Handle Type:	Knob
Lock Type:	Padlockable
Maximum Mounted Auxiliary Contacts:	2 NO, 2 NC
Mounting Type:	Base/DIN mounting
Number of Poles:	4P
Operating Mode:	Front
Position of Line Terminals:	Top In - Bottom Out Bottom In - Top Out
Power Loss:	at Rated Operating Conditions per Pole 4.6 W
Rated Conditional Short-Circuit Current (I_{nc}):	(80 A fuse, 690 V) 25 kA
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Insulation Voltage (U_i):	acc. to IEC 60947-1 800 V
Rated Operational Current AC-21A (I_e):	(415 V) 125 A (690 V) 125 A (800 V) 80 A
Rated Operational Current AC-22A (I_e):	(415 V) 125 A (690 V) 125 A (800 V) 63 A
Rated Operational Current AC-23A (I_e):	(415 V) 125 A (690 V) 63 A
Rated Operational Power AC-23A (P_e):	(415 V) 55 kW (690 V) 55 kW
Rated Operational Voltage:	Main Circuit 800 V
Rated Short-Circuit Making Capacity (I_{cm}):	(690 V) 4.8 kA
Rated Short-time Withstand Current Low Voltage (I_{cw}):	for 1 s 2.5 kA for 0.2 s 3.2 kA
Recommended Screw Driver:	Main Circuit Hexagon 4
Special Functions:	No
Standards:	IEC60947-3
Switches Operating Mechanism:	Mechanism on Top of the Switch
Terminal Type:	Screw Terminals
Tightening Torque:	acc. IEC 60947-1 6 N·m
Wire Stripping Length:	Main Circuit 16-18 mm Main Circuit 0.63-0.71 in

Technical UL/CSA

Tightening Torque UL/CSA:	UL 53 N·m
----------------------------------	-----------

Certificates and Declarations

CCC Certificate:	CCC OTC30-160G3
Declaration of Conformity - CE:	1SCC303136D2701

External Classifications and Standards

Object Classification Code:	Q
ETIM 9:	EC000216 - Switch disconnecter (low voltage)
ETIM 10:	EC000216 - Switch disconnecter (AC)
UNSPSC:	39122233
IDEA Granular Category Code (IGCC):	5290 >> Disconnect switch
eClass:	V11.1 : 27371403
WEEE Category:	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland):	3642600
E-Number (Norway):	4384824

Categories

Products > Low Voltage Products and Systems > Switches > Change-over and Transfer Switches > Manual Change-over Switches

