

Product data sheet

Characteristics

1150002

Thorsman - TPS-6/5x35 - nail plug - with screw - set of 100



Main

Range of product	Thorsman
Product or component type	Nail plug
Device short name	TPS
Provided equipment	Screw
Drilling diameter	6 mm
Minimum drilling depth	42 mm
Screw diameter	3.5 mm

Complementary

Colour tint	Clear
Material	Nail plug: PA (polyamide) Screw: steel electroplated
Practical load capacity	Shear: 0.4 kN for concrete C25 4.5) Pull-out load: 0.2 kN for concrete C25 6) Shear: 0.4 kN for solid brick 4.5) Pull-out load: 0.2 kN for solid brick 6) Shear: 0.1 kN for low density concrete 500 and expanded clay 4.5) Pull-out load: 0.07 kN for low density concrete 500 and expanded clay 6)
Thickness	0...5 mm fixture
Ambient air temperature for operation	-40...80 °C
Diameter	10 mm
Length	60 mm

Environment

Quantity per set	Set of 100
Net weight	0.0038 kg

Packing Units

Package 1 Weight	3.800 g
Package 1 Height	10.000 mm
Package 1 width	10.000 mm
Package 1 Length	60.000 mm

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------