



Main

Range name	Sedna
Function	Socket-outlet
Delivery form	Complete product
Outlet poles configuration	2P + E with shutters
Outlet standard description	Side earth
Rated current	16 A at 250 V AC

Complementary

Power range	3680 W
Kind of terminals	Lift terminals
Terminal capacity	2 cable(s) 2.5 mm ²
Wire structure	Flexible Rigid Solid stranded
Wire stripping length	13 mm
Material of visible parts	ASA + PC
Surface finish	Glossy
Fixing mode	Claws, span of claws working range: 52...69 mm Screws
Height	120 mm
Width	84 mm
Depth	48 mm
Depth of visual part	23.3 mm
Net weight	0.1031 kg

Environment

Standards	IEC 60884-1
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	102 g
Package 1 Height	4.2 cm
Package 1 width	8.2 cm
Package 1 Length	11.9 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.134 kg
Package 2 Height	10 cm
Package 2 width	20.5 cm
Package 2 Length	31.5 cm
Unit Type of Package 3	CAR

Number of Units in Package 3	50
Package 3 Weight	6.023 kg
Package 3 Height	53.5 cm
Package 3 width	21.5 cm
Package 3 Length	32 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------