



Main

Range of product	Exxact Surface
Range	Exxact
Product or component type	Socket-outlet
Device presentation	Complete product
Quantity per set	Set of 5

Complementary

Device mounting	Surface
Socket number	4
Outlet poles configuration	2P + E with shutters
Rated current/voltage	16 A at 250 V AC
Colour	White (RAL 9003)
Connections - terminals	Screw terminals
Shape of screw head	Pozidriv No 1 and combi
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² for solid cable(s) 1 x 1.5...2 x 2.5 mm ² for solid stranded cable(s)
Material	PC (polycarbonate): cover frame PC 10 % GF: bottom-plate
Optional fixing mode	By screws: insert By screws: cover frame
Function available	Possibility for two loop connections
Embedding depth	0.0 mm
Height	98.0 mm
Width	116.0 mm
Projecting depth	42.0 mm

Environment

Standards	DIN VDE 0620-1 IEC 60884-1 NEK 502 SFS 5610 SS 4280834
Product certifications	FIMKO NEMKO SEMKO CE
IP degree of protection	IP20 also with visual parts removed IP21 when cable is coming from below

Packing Units

Package 1 Weight	1.000 g
Package 1 Height	43.000 mm
Package 1 width	116.000 mm
Package 1 Length	98.000 mm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins