



Main

Range	Unica
Product or component type	Trailing lead
Aesthetic name	Unica extend
Control type	Mains switch
Socket number	3
Number of power socket outlets	3 square
Integrated connection type	2 USB port 5 V DC, maximum load current: 2.4 A
Cable length	3 m
Colour tint	Anthracite

Complementary

Number of socket outlets with earth pin	3
[Ue] rated operational voltage	250 V
Number of USB connection	2
[In] rated current	16 A
Outlet poles configuration	2P + E
Outlet standard	Schuko
Socket additional information	Shuttered
Maximum switching capacity	16 A
Pilot light	ON indicator
Material	PP (polypropylene)
Length	254 mm
Width	57 mm
Depth	40.5 mm
Quantity per set	Set of 1
Type of packing	Blister

Packing Units

Package 1 Weight	579.000 g
Package 1 Height	53.000 mm
Package 1 width	136.000 mm
Package 1 Length	330.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Environmental Disclosure

 [Product Environmental Profile](#)

Circularity Profile

 [End Of Life Information](#)
