



### Main

Range of product	Mureva Styl
Product or component type	Rocker switch
Device presentation	Complete product
Colour tint	Grey (RAL 7016)

### Complementary

Device mounting	Surface
Switch function	Double 2-way
Actuator	Rocker
Rated current	10 AX
Load type	Load for energy saving lamps with ballast: 100 W
[Ue] rated operational voltage	250 V AC
Condition of use	Indoor/outdoor
Material	SEBS Brass ABS (acrylonitrile butadiene-styrene)
Fixing mode	By screws
Clamping connection capacity	1.5...2.5 mm <sup>2</sup> for rigid cable(s) 1.5...2.5 mm <sup>2</sup> for stranded cable(s) 1.5...2.5 mm <sup>2</sup> for flexible cable(s)
Wire stripping length	13 mm
Cable entry	Easy valve access diameter: 6...20 mm
Chemical and detergent products resistance	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane
Height	76 mm
Width	76 mm
Depth	64 mm
Projecting depth	64 mm

## Environment

Quality labels	CE NF AENOR EAC
IP degree of protection	IP55
IK degree of protection	IK08
Flame retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
Standards	EN 60669-1
Ambient air temperature for operation	-5...40 °C
Ambient air temperature for storage	-25...55 °C

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>