



Main

Range of product	Renova
Range	Renova
Product or component type	Switch
Device application	Control
Device presentation	Insert + rocker
Colour tint	Black (NCS S 9000-N)
Quantity per set	Set of 5

Complementary

Product compatibility	To be completed with Renova frame
Rated current	16 A
[Ue] rated operational voltage	250 V AC
Connections - terminals	Screwless terminals
Number of loop terminals	2
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² for solid cable(s) 1 x 1.5...2 x 2.5 mm ² for solid stranded cable(s)
Switch function	Intermediate
Switch pattern	[7]
Actuator	Rocker
Device mounting	Flush
Material	PC/ABS
Fixing mode	By claws By screws
Diameter	71 mm
Embedding depth	15 mm
Projecting depth	19 mm

Environment

IP degree of protection	IP20 also with visual parts removed
Product certifications	NEMKO CE SEMKO FIMKO
Standards	EN 60669-1

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	72 g
Package 1 Height	5 cm
Package 1 width	7 cm
Package 1 Length	7 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	5

Package 2 Weight	860 g
Package 2 Height	8.5 cm
Package 2 width	8.5 cm
Package 2 Length	22.5 cm
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Weight	4.703 kg
Package 3 Height	21 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins