



Main

Range of product	Sedna
Product or component type	USB charger
Integrated connection type	2 USB 2.0 port 5 V DC, maximum load current: 2.1 A

Complementary

Device application	Charger
Device mounting	Flush
Device presentation	Mechanism with fixing frame
Surface treatment	Untreated
Number output current	2.1 A
Fixing mode	By claws
Type of packing	Flow-pack
[Ue] rated operational voltage	100...240 V AC +/- 10 % at 50/60 Hz
Maximum power consumption in W	0.1 W
Nominal output power	10.5 W
Input power	12 W
Service life in hours	30000 h 10.5 W
Material	ABS (acrylonitrile butadiene-styrene): centre plate PC (polycarbonate) GF10 FR: casing PC (polycarbonate) GF10 FR: internal cover
Protection type	Short-circuit protection
Number of terminals	2 screw terminals
Clamping connection capacity	2 x 0.75...2 x 2.5 mm ² for rigid cable(s) 2 x 0.75...2 x 2.5 mm ² for flexible cable(s) 2 x 0.75...2 x 2.5 mm ² for stranded cable(s)
Wire stripping length	8 mm
Product compatibility	Mobile/Tablet Mac iOS Mobile/tablet Windows
Height	71 mm
Width	71 mm
Depth	37 mm
Embedding depth	30.8 mm

Environment

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-5...50 °C
Standards	ETSI EN 301 489-4
Directives	2002/95/EC - RoHS directive
Product certifications	EAC
Electrical insulation class	Class II

IK degree of protection	IK04
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	113 g
Package 1 Height	8.4 cm
Package 1 width	6.3 cm
Package 1 Length	12.9 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	36
Package 2 Weight	4.473 kg
Package 2 Height	19 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins