



Main

| | |
|-----------------------------|------------------|
| Range | Asfora |
| Product or component type | Socket-outlet |
| Outlet standard description | Side earth |
| Outlet poles configuration | 2 x 2P + E |
| Device presentation | Complete product |
| Colour tint | White |
| Type of packing | Flow-pack |



Complementary

| | |
|-------------------------|---|
| Socket number | 2 |
| Device mounting | Flush |
| Power range | 3680 W |
| Rated current | 16 A at 250 V AC |
| Connections - terminals | Lift terminals |
| Number of cables | 2 cable(s) 2.5 mm ² |
| Cable stiffness | Solid stranded Rigid Flexible |
| Wire stripping length | 11 mm |
| Material | ABS (acrylonitrile butadiene-styrene): cover frame ASA + PC: central plate |
| Surface finish | Glossy |
| Conductor material | Copper |
| Fixing mode | Claws54...72 mm |
| Height | 123 mm |
| Width | 83 mm |
| Depth | 46 mm |
| Projecting depth | 23 mm |
| Quantity per set | 1 |

Environment

| | |
|-------------------------|-------------|
| Standards | IEC 60884-1 |
| Product certifications | VDE UKR |
| IP degree of protection | IP20 |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |

| | |
|----------------------------|---|
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |