



Main

Range name	Sedna Design & Elements
Range	Sedna
Function	USB charger + socket-outlet
Device mounting	Flush
Delivery form	Mechanism with fixing frame
Type of packing	Box
Outlet poles configuration	2P + E
Outlet standard description	Side earth
Outlet standard	European
Rated current	16 A at 250 V AC
Colour	Beige
Colour code	RAL 1013
Quantity per set	1 piece

Complementary

Power range	3680 W
Integrated connection type	2 USB 2.0 port 5 V DC, maximum load current: 2.1 A
Kind of terminals	Screwless terminals
Terminal capacity	2 cable(s) 2.5 mm ²
Wire structure	Rigid or flexible
Wire stripping length	13 mm
Material of visible parts	PC
Surface finish	Glossy
Fixing mode	Screws or claws, span of claws working range: 55...67 mm Claws, span of claws working range: 52...69 mm
Height	71 mm
Width	71 mm
Depth	44 mm
Depth of visual part	32 mm
Net weight	0.096 kg

Environment

Standards	IEC 60884-1
Conformity mark	CE KEMA-KEUR EAC
Product certifications	VDE FIMKO NEMKO AENOR
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	117 g
Package 1 Height	6 cm
Package 1 width	7.5 cm
Package 1 Length	7.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	54
Package 2 Weight	6.741 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	864
Package 3 Weight	119.856 kg
Package 3 Height	75 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product