



Main

Range name	Sedna Design & Elements
Range	Sedna
Function	Socket-outlet
Device mounting	Flush
Delivery form	Complete product
Type of packing	Flow-pack
Outlet poles configuration	2 x 2P + E with shutters
Outlet standard description	Side earth
Outlet standard	European
Rated current	16 A at 250 V AC
Colour	Beige
Colour code	RAL 1013
Quantity per set	1 piece

Complementary

Power range	3680 W
Kind of terminals	Screwless terminals
Terminal capacity	2 cable(s) 2.5 mm ²
Wire structure	Rigid
Wire stripping length	13 mm
Material of visible parts	PC
Surface finish	Glossy
Fixing mode	Screws or claws, span of claws working range: 52...77 mm Claws, span of claws working range: 52...69 mm
Height	85 mm
Width	120 mm
Depth	49 mm
Depth of visual part	24 mm
Net weight	0.095 kg

Environment

Standards	IEC 60884-1
Conformity mark	CE EAC
Product certifications	VDE AENOR
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	99 g
Package 1 Height	5 cm
Package 1 width	8.5 cm
Package 1 Length	12 cm

Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Weight	872 g
Package 2 Height	9.5 cm
Package 2 width	18.5 cm
Package 2 Length	27.5 cm
Unit Type of Package 3	S04
Number of Units in Package 3	96
Package 3 Weight	11.105 kg
Package 3 Height	30 cm
Package 3 width	40 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product