## ALB45287

# Altira - 1 SO - 2P+E with shutters - side earth - white





Main	
Range	Altira
Product or component type	Socket-outlet
Range compatibility	Fixing frame Fixing frame
Device presentation	Mechanism
Number of power socket outlets	1 x 2P + E, German
Outlet standard description	Side earth
Socket additional information	Shuttered
Colour tint	Cover plate: white (RAL 9010)

#### Complementary

Product destination	Fixing frames	
Range compatibility	OptiLine 45 OptiLine 70 with Altira adaptor	
Ground lug position	Straight 90° position	
Rated current	16 A at 250 V AC 50/60 Hz	
Number of modules	2 modules	
Connections - terminals	Screwless terminals	
Clamping connection capacity	4 x 1.54 x 2.5 mm² for rigid cable(s) 4 x 1.54 x 2.5 mm² for solid stranded cable(s)	
Material	PC: mechanism cover	
Surface treatment	Untreated	
Surface finish	Satin	
Standards	NF C 61-314 EN 62262 EN 60529 IEC 60884-1	
Height	45 mm	
Width	45 mm	
Depth	39 mm	

#### Environment

Ambient air temperature for operation	550 °C
Ambient air temperature for storage	-1560 °C
IK degree of protection	IK02
IP degree of protection	IP20
Environmental characteristic	Alcohol Petrol Bleach UV resistant Oil Window-cleaning fluid Hydrogen peroxide (H2O2) Ammonia Liquid soap Acetone

### Packing Units

•	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	32.3 g
Package 1 Height	4 cm
Package 1 width	4.5 cm
Package 1 Length	4.5 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	364.4 g
Package 2 Height	9 cm
Package 2 width	9 cm
Package 2 Length	21.5 cm
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Weight	4.887 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

#### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation		
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

#### Contractual warranty

Warranty	18 months
----------	-----------