



### Main

Range name	Sedna Design & Elements
Range	Sedna
Function	USB charger + socket-outlet
Device mounting	Flush
Delivery form	Mechanism with fixing frame
Type of packing	Box
Outlet poles configuration	2P + E
Outlet standard description	Side earth
Outlet standard	European
Rated current	16 A at 250 V AC
Colour	White
Colour code	RAL 9003
Quantity per set	1 piece

### Complementary

Power range	3680 W
Integrated connection type	2 USB 2.0 port 5 V DC, maximum load current: 2.1 A
Kind of terminals	Screwless terminals
Terminal capacity	2 cable(s) 2.5 mm <sup>2</sup>
Wire structure	Rigid or flexible
Wire stripping length	13 mm
Material of visible parts	PC
Surface finish	Glossy
Fixing mode	Screws or claws, span of claws working range: 55...67 mm Claws, span of claws working range: 52...69 mm
Height	71 mm
Width	71 mm
Depth	44 mm
Depth of visual part	32 mm
Net weight	0.096 kg

### Environment

Standards	IEC 60884-1
Conformity mark	CE KEMA-KEUR EAC
Product certifications	VDE FIMKO NEMKO AENOR
IP degree of protection	IP20

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	115 g
Package 1 Height	6 cm
Package 1 width	7.5 cm
Package 1 Length	7.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	54
Package 2 Weight	6.641 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	864
Package 3 Weight	118.256 kg
Package 3 Height	72 cm
Package 3 width	80 cm
Package 3 Length	120 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Halogen content performance	Halogen free product