



Main

| | |
|--------------------------------|--------------------------|
| Range of product | Acti 9 |
| Product name | Acti 9 iCT |
| Product or component type | Contacteur |
| Device short name | ICT |
| Device application | Motor-heating-lighting |
| Poles | 4P |
| [Ie] rated operational current | 40 A AC-7A 15 A AC-7B |
| Pole contact composition | 4 NO |
| Network type | AC |
| Control type | Remote control |
| [Uc] control circuit voltage | 220...240 V AC 50 Hz |

Complementary

| | |
|--|--|
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 400 V AC 50 Hz |
| Maximum power | 2.1 W at 400 V AC |
| [Ui] rated insulation voltage | 500 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Control signal type | Maintained |
| Switching frequency | 100 switching operations/day |
| Local signalling | Action indicator |
| Hold-in power consumption in VA | 6.5 VA |
| Inrush power in VA | 53 VA |
| Mounting mode | Clip-on |
| Mounting support | 35 mm symmetrical DIN rail |
| 9 mm pitches | 6 |
| Height | 85 mm |
| Width | 54 mm |
| Depth | 60 mm |
| Colour | White |
| Mechanical durability | 1000000 cycles |
| Electrical durability | 100000 Cycles IEC/EN 61095 40 A 50 Hz AC-7A 30000 Cycles IEC/EN 61095 15 A 50 Hz AC-7B 30000 Cycles IEC/EN 61095 50 Hz AC-7C 100000 Cycles EN/IEC 60947-4-1 50 Hz AC-1 30000 Cycles EN/IEC 60947-4-1 50 Hz AC-3 30000 Cycles EN/IEC 60947-4-1 50 Hz AC-5a 30000 cycles EN/IEC 60947-4-1 50 Hz AC-5b |
| Connections - terminals | Control circuit: tunnel type terminals2 cable(s) 1.5 mm ² rigid Control circuit: tunnel type terminals1 cable(s) 1.5...2.5 mm ² rigid Power circuit: tunnel type terminals1 cable(s) 6...16 mm ² flexible Power circuit: tunnel type terminals1 cable(s) 6...25 mm ² rigid Control circuit: tunnel type terminals2 cable(s) 1.5...2.5 mm ² flexible |
| Tightening torque | Control circuit: 0.8 N.m Power circuit: 3.5 N.m |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|-----------------------|----------------------------------|
| Product compatibility | IACTp IATeT IACTc IACTs |
| Compatibility code | ICT |
| Market segment | Residential Small commercial |

Environment

| | |
|---------------------------------------|--|
| Standards | IEC/EN 61095 |
| Noise level | 30 dB |
| Heat dissipation | 2.1 W at 50/60 Hz |
| IP degree of protection | IP20 |
| Pollution degree | 2 |
| Tropicalisation | 2 conforming to EN 60947-4-1 2 conforming to EN 61095 2 conforming to IEC 1095 |
| Relative humidity | 95 % at 55 °C |
| Operating altitude | 2000 m |
| Ambient air temperature for operation | -5...60 °C |
| Ambient air temperature for storage | -40...70 °C |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 361 g |
| Package 1 Height | 6 cm |
| Package 1 width | 11 cm |
| Package 1 Length | 12 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 4 |
| Package 2 Weight | 1.521 kg |
| Package 2 Height | 13 cm |
| Package 2 width | 12 cm |
| Package 2 Length | 25 cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 24 |
| Package 3 Weight | 9.613 kg |
| Package 3 Height | 30 cm |
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|