


# DISC LED

## Product Group: High-bays



**Description:** A budget LED high-bay luminaire with lens optic for high mounting applications  
Optics: 90° light beam, polycarbonate, impact resistance  
Body: die-cast aluminum, black finish

**General data:** Mains voltage: 220-240V, 50-60Hz  
Power factor: >0,90  
Light source: LED  
Light source included: Yes  
Light distribution type: Direct  
LED lifetime, h: 50000/L70B50  
Operating temperature range, °C: ta -25...+40  
Protection class IEC: I  
Ingress protection code: IP65  
Mechanical impact resistance: IK08  
EEC: A++

**Installation:** Suspended. Supplied with suspension hook and out-going cable for easy mounting. Cable, 0,3m, 3x1.0mm2

**Environment:** Indoor


**Application:** Industry, warehouse, hall

Product	Length, mm	Width, mm	Height, mm	Luminaire output*, lm	System power*, W	System efficacy*, lm/W	CRI	CCT*, K	Weight, kg
Disc LED1x14000 E927 T840	290	290	118	14000	100,0	140	80+	4000	2,35
Disc LED1x21000 E928 T840	336	336	127	21000	150,0	140	80+	4000	2,40
Disc LED1x28000 E929 T840	376	376	131	28000	200,0	140	80+	4000	3,70

\* tolerance range for optical and electrical data: ±10%. Values apply to an ambient temperature of 25°C

**Available options:**

T840 Colour temperature 4000K, CRI 80+



**Available accessories:**



Product: Power supply connector - IP66/IP68, 3x1.5mm2  
Description: Quick and easy to connect power supply and luminaire cables connector - IP66/IP68, 3x1.5mm2, 400V/16A, 1pcs



Product: Suspension MTG KIT - Saturn LED 1.5m  
Description: Suspension kit for Saturn LED high-bay, 1.5 meter  
Product: Suspension MTG KIT - Saturn LED 3.0m  
Description: Suspension kit for Saturn LED high-bay, 3.0 meter  
Product: Suspension MTG KIT - Saturn LED 5.0m  
Description: Suspension kit for Saturn LED high-bay, 5.0 meter