



Home Surveillance System

Network Video Recorder Kit..... 1
 Digital Video Recorder Kit.....2-3

Professional Surveillance System

Megapixel IP Camera.....4-7
 Network Video Recorder.....8
 Array IR Led Day&Night Camera.....9-12
 IR Led Day&Night Camera.....13-16
 Color Dome Camera..... 17
 Vandal-proof Dome Camera.....18-19
 Box Camera.....20
 Special Camera.....21
 Speed Dome Camera.....22-24
 Digital Video Recorder.....25-27

CCTV Accessories

Accessories.....28-30

CONTENTS



Kit Includes:

- ◆ 1*4-CH 4CH H.264 720P/960P real time NVR, with Power over Ethernet function(SE-NR8104DP)
- ◆ 4*IP IR camera, with Power over Ethernet function (SE-NI102VH),1 megapixel, 1/4" progressive scan CMOS,720P@25fps,IR-CUT,with 3.6mm lens, 30 leds,20-30m IR Distance
- ◆ 1*Power Adaptor for NVR
- ◆ 4*60 feet CAT5E Ethernet Cable


Item No.: SE-NR8104DP-NI102VH



Kit Includes:

- ◆ 1*4-CH 4CH H.264 720P/960P real time NVR, with Power over Ethernet function(SE-NR8104DP)
- ◆ 4*IP IR camera, with Power over Ethernet function (SE-NA104VH),1 megapixel, 1/4" progressive scan CMOS,720P@25fps,IR-CUT,with 3.6mm lens, 2 Array leds,30-40m IR Distance
- ◆ 1*Power Adaptor for NVR
- ◆ 4*60 feet CAT5E Ethernet Cable

Item No.: SE-NR8104DP-NA104VH



Kit Includes:

- ◆ 1*4-CH 4CH H.264 720P/960P real time NVR, with Power over Ethernet function(SE-NR8104DP)
- ◆ 4*IP IR camera, with Power over Ethernet function (SE-ND102PH),1 megapixel, 1/4" progressive scan CMOS,720P@25fps,IR-CUT,with 3.6mm lens, 12 leds,15-20m IR Distance
- ◆ 1*Power Adaptor for NVR
- ◆ 4*60 feet CAT5E Ethernet Cable

Item No.: SE-NR8104DP-ND102PH



Item No.: SE-RD614H-CD342C

Kit Includes:

- ◆ 1*4-CH H.264 mobile surveillance DVR(SE-RD614H)
 - ◆ 4*color 1/4" HD Digital Sensor IR dome camera (SE-CD342C)700TVL with 3.6mm lens,24 leds,10-15m IR Distance IR cut filter optional
 - ◆ 2*Integrative power adapters for DVR and cameras
 - ◆ 4*60 feet cable with V/DC
 - ◆ Other accessories
- Optional camera:
color 1/4" HD Digital Sensor IR camera (SE-CI341H)700TVL

Note:8-CH DVR kit is available



Item No.: SE-RD634D-CI341H

Kit Includes:

- ◆ 1*4-CH H.264 mobile surveillance DVR(SE-RD634D),with HDMI
 - ◆ 4*color 1/4" HD Digital Sensor IR camera (SE-CI341H)700TVL with 3.6mm lens,24 leds,10-15m IR Distance IR cut filter optional
 - ◆ 2*Integrative power adapters for DVR and cameras
 - ◆ 4*60 feet cable with V/DC
 - ◆ Other accessories
- Optional camera:
color 1/4" HD Digital Sensor IR dome camera (SE-CD342C)700TVL
color 1/4" HD Digital Sensor IR camera (SE-CI342V)700TVL

Note:8-CH DVR kit is available



Item No.: SE-RD624V-CI142V

Kit Includes:

- ◆ 1*4-CH H.264 mobile surveillance DVR(SE-RD624V)
 - ◆ 4*color 1/3" Sony CCD IR camera (SE-CI142V)500TVL with 3.6mm lens,30 leds,20-30m IR Distance
 - ◆ 2*Integrative power adapters for DVR and cameras
 - ◆ 4*60 feet cable with V/DC
 - ◆ Other accessories
- Optional camera:
color 1/4" HD Digital Sensor IR dome camera (SE-CD342C)700TVL
color 1/4" HD Digital Sensor IR camera (SE-CI341H)700TVL

Note:8-CH DVR kit is available



Item No.: SE-RM6245-CI341H

Kit Includes:

- ◆ 1*15" LCD 4-CH Integrative H.264 mobile surveillance DVR (SE-RM6245)
 - ◆ 4*color 1/4" HD Digital Sensor IR camera (SE-CI341H)700TVL with 3.6mm lens,24 leds,10-15m IR Distance IR cut filter optional
 - ◆ 2*Integrative power adapters for DVR and cameras
 - ◆ 4*60 feet cable with V/DC
 - ◆ Other accessories
- Optional camera:
color 1/4" HD Digital Sensor IR dome camera (SE-CD342C)700TVL



Item No.: SE-RD6047-CI311Q

Kit Includes:

- ◆ 1*7" LCD 4-CH DVR (SE-RD6047), Wireless MPEG4 mobile surveillance
- Specification:
Frequency: 2.4GHz ISM, 25FPS
LCD Display: 800x480 Resolution
Recording Mode: Manual/Schedule/Motion Detection
Two way audio with loudspeaker
Support to 32G Micro SD Card
Power Supply: DC 5V/1A
- ◆ 4*color 1/4" CMOS IR wireless camera (SE-CI311Q), 12 leds,10-15m IR distance
 - ◆ Transmission Range: 150m (Open Area)
 - ◆ Other accessories



Item No.: SE-RD6345-CI132I

Kit Includes:

- ◆ 1*15" LCD Integrative, 4-CH Wireless H.264 mobile surveillance DVR (SE-RM6345)
- ◆ 4*color 1/3" Sony CCD IR Wireless camera (SE-CI132I) 420TVL,with 3.6mm lens, 24 leds,15-20m IR Distance
- ◆ Transmission Range: 100m



SE-NC100C 1 Mega Pixel, 1/4" CMOS
SE-NC100CW 1 Mega Pixel, 1/4" CMOS, built-in wifi

- ◆ P2P IP camera
- ◆ Video compression: H.264 Main Profile/Baseline
- ◆ Audio compression: G711/G726
- ◆ Resolution: 720P(1280*720)
- ◆ Supports network self-adapting technology to adjust video frame rate automatically according to the network bandwidth, 1-30fps adjustable per second
- ◆ Support AVI, ASF, H.264 playback
- ◆ Built-in IR-CUT, IR distance: 12m, illumination: 0.11LUX
- ◆ Built-in microphone and loudspeaker, supports two-way audio intercom communication
- ◆ Supports privacy protection mode, motion detection and sensor alarm functions
- ◆ Support RJ45 10/100M
- ◆ Support iPhone, Android smart phone



SE-ND031A 0.3 Mega Pixel, CMOS sensor
SE-ND101A 1 Mega Pixel, CMOS sensor

- ◆ Wireless P2P IP camera
- ◆ H.264 video compression
- ◆ Plug and play, easy setting
- ◆ 10pcs IR Leds, 15M IR distance 6mm lens
- ◆ Embedded independently-developed cloud system(icloudCam)
- ◆ Scan the QRcode of cameras to connect with mobile phone easily
- ◆ Two-way audio intercom communication
- ◆ Build in infrared for day and night monitoring
- ◆ Built-in IR-CUT, the filter switch automatically



SE-ND102P 1 megapixel, 1/4" CMOS (TI Davinci DM365); 720P@25fps; IR-CUT
SE-ND132P 1.3 megapixel, 1/3" CMOS (TI Davinci DM365); 1080P@5fps, 960P@25fps, 720P@25fps; IR-CUT
SE-ND202P 2-5 megapixel, 1/2.5" CMOS (TI Davinci DM368); 5MP@10fps, 3MP@15fps, 1080P@25fps; IR-CUT
SE-ND102PH 1 megapixel, 1/4" CMOS (Hisilicon 3518C); 720P@25fps; IR-CUT
SE-ND132PH 1.3 megapixel, 1/3" CMOS (Hisilicon 3518C); 1080P@5fps, 960P@25fps, 720P@25fps; IR-CUT
 H.264 Dual-stream Encoding
 IR Distance :15-20M
 IR Led: \varnothing 5*12pcs
 Lens: MTV Lens 3.6/6mm



SE-ND103H 1 megapixel, 1/4" CMOS (TI Davinci DM365); 720P@25fps; IR-CUT
SE-ND133H 1.3 megapixel, 1/3" CMOS (TI Davinci DM365); 1080P@5fps, 960P@25fps, 720P@25fps; IR-CUT
SE-ND203H 2-5 megapixel, 1/2.5" CMOS (TI Davinci DM368); 5MP@10fps, 3MP@15fps, 1080P@25fps; IR-CUT
 H.264 Dual-stream Encoding
 IR Distance :30M
 IR Led: \varnothing 5*42pcs
 Lens: CS Lens 4/6/8mm
Note: PoE function is optional



SE-NI102VH 1 megapixel, 1/4" CMOS (Hisilicon 3518C); 720P@25fps; IR-CUT
SE-NI132VH 1.3 megapixel, 1/3" CMOS (Hisilicon 3518C); 1080P@5fps, 960P@25fps, 720P@25fps; IR-CUT
 H.264 Dual-stream Encoding
 IR Distance :20-30M
 IR Led: \varnothing 5*30pcs
 Lens: MTV Lens 6/3.6/8/12mm



SE-NA104VH 1 megapixel, 1/4" CMOS (Hisilicon 3518C); 720P@25fps; IR-CUT
SE-NA134VH 1.3 megapixel, 1/3" CMOS (Hisilicon 3518C); 1080P@5fps, 960P@25fps, 720P@25fps; IR-CUT
 H.264 Dual-stream Encoding
 IR Distance :30-40M
 IR Led: 42MIL*2pcs Array IR Led
 Lens: MTV Lens 6/3.6/8/12mm



SE-NA106R 1 megapixel, 1/4" CMOS (TI Davinci DM365); 720P@25fps; IR-CUT
SE-NA136R 1.3 megapixel, 1/3" CMOS (TI Davinci DM365); 1080P@5fps, 960P@25fps, 720P@25fps; IR-CUT
SE-NA206R 2-5 megapixel, 1/2.5" CMOS (TI Davinci DM368); 5MP@10fps, 3MP@15fps, 1080P@25fps; IR-CUT
SE-NA106RH 1 megapixel, 1/4" CMOS (Hisilicon 3518C); 720P@25fps; IR-CUT
SE-NA136RH 1.3 megapixel, 1/3" CMOS (Hisilicon 3518C); 1080P@5fps, 960P@25fps, 720P@25fps; IR-CUT
 H.264 Dual-stream Encoding
 IR Distance :40-60M
 IR Led: 42MIL*1pc Array IR Led
 Lens: CS Lens 6/4/8mm



SE-NA108R 1 megapixel, 1/4" CMOS (TI Davinci DM365); 720P@25fps; IR-CUT
SE-NA138R 1.3 megapixel, 1/3" CMOS (TI Davinci DM365); 1080P@5fps, 960P@25fps, 720P@25fps; IR-CUT
SE-NA208R 2-5 megapixel, 1/2.5" CMOS (TI Davinci DM368); 5MP@10fps, 3MP@15fps, 1080P@25fps; IR-CUT
SE-NA108RH 1 megapixel, 1/4" CMOS (Hisilicon 3518C); 720P@25fps; IR-CUT
SE-NA138RH 1.3 megapixel, 1/3" CMOS (Hisilicon 3518C); 1080P@5fps, 960P@25fps, 720P@25fps; IR-CUT
 H.264 Dual-stream Encoding
 IR Distance :60-80M
 IR Led: 42MIL*2pcs Array IR Led
 Lens: CS Lens 8/6/12mm

 <p>SE-NA104T 1 megapixel, 1/4"CMOS (TI Davinci DM365); 720P@25fps;IR-CUT SE-NA134T 1.3 megapixel, 1/3"CMOS (TI Davinci DM365);1080P@5fps, 960P@25fps, 720P@25fps;IR-CUT SE-NA204T 2-5 megapixel, 1/2.5"CMOS (TI Davinci DM368);5MP@10fps, 3MP@15fps, 1080P@25fps;IR-CUT SE-NA104TH 1 megapixel, 1/4" CMOS (Hisilicon 3518C);720P@25fps;IR-CUT SE-NA134TH 1.3 megapixel, 1/3" CMOS (Hisilicon 3518C);1080P@5fps, 960P@25fps, 720P@25fps;IR-CUT H.264 Dual-stream Encoding IR Distance :30-50M IR Led: 42MIL×2pcs Array IR Led Lens: MTV Lens 3.6/6/8mm Note:PoE function is optional</p>	 <p>SE-NA106T 1 megapixel, 1/4"CMOS (TI Davinci DM365); 720P@25fps;IR-CUT SE-NA136T 1.3 megapixel, 1/3"CMOS (TI Davinci DM365);1080P@5fps, 960P@25fps, 720P@25fps;IR-CUT SE-NA206T 2-5 megapixel, 1/2.5"CMOS (TI Davinci DM368);5MP@10fps, 3MP@15fps, 1080P@25fps;IR-CUT SE-NA106TH 1 megapixel, 1/4" CMOS (Hisilicon 3518C);720P@25fps;IR-CUT SE-NA136TH 1.3 megapixel, 1/3" CMOS (Hisilicon 3518C);1080P@5fps, 960P@25fps, 720P@25fps;IR-CUT H.264 Dual-stream Encoding IR Distance :50-70M IR Led: 42MIL×3pcs Array IR Led Lens: CS Lens 4/6/8mm</p>
 <p>SE-NA108T 1 megapixel, 1/4"CMOS (TI Davinci DM365); 720P@25fps;IR-CUT SE-NA138T 1.3 megapixel, 1/3"CMOS (TI Davinci DM365);1080P@5fps, 960P@25fps, 720P@25fps;IR-CUT SE-NA208T 2-5 megapixel, 1/2.5"CMOS (TI Davinci DM368);5MP@10fps, 3MP@15fps, 1080P@25fps;IR-CUT SE-NA108TH 1 megapixel, 1/4" CMOS (Hisilicon 3518C);720P@25fps;IR-CUT SE-NA138TH 1.3 megapixel, 1/3" CMOS (Hisilicon 3518C);1080P@5fps, 960P@25fps, 720P@25fps;IR-CUT H.264 Dual-stream Encoding IR Distance :80-100M IR Led: 42MIL×4pcs Array IR Led Lens: CS Lens 4/6/8mm</p>	 <p>SE-NB100A 1 megapixel, 1/4"CMOS (TI Davinci DM365); 720P@25fps;IR-CUT SE-NB130A 1.3 megapixel, 1/3"CMOS (TI Davinci DM365);1080P@5fps, 960P@25fps, 720P@25fps;IR-CUT SE-NB200A 2-5 megapixel, 1/2.5"CMOS (TI Davinci DM368);5MP@10fps, 3MP@15fps, 1080P@25fps;IR-CUT SE-NB100AH 1 megapixel, 1/4" CMOS (Hisilicon 3518C);720P@25fps;IR-CUT SE-NB130AH 1.3 megapixel, 1/3" CMOS (Hisilicon 3518C);1080P@5fps, 960P@25fps, 720P@25fps;IR-CUT H.264 Dual-stream Encoding Real-time video transmission Motion detection and IO alarm linkage front-end storage With ICR, DNR (Super Digital Noise Reduction) Note:Built-in low power WiFi module optional</p>

HD IP Speed Dome Camera fitting selectable---Integrative zoom camera

BRAND	SPECIFICATION	
SECUEASY	1.3MP, 1/3" interlacing scan CCD, 18x HD camera, Color to B/W, 720P full HD output	
HITACHI	1.3MP, 1/3" interlacing scan CCD, 18x HD camera, Color to B/W, 720P full HD output, 0.02 Lux, 4.7-84.6mm WDR function	
SONY	2.0MP, 1/2.8 inch Exmor TM CMOS, 18x HD camera, Color to B/W, 1080P full HD output, 0.01 Lux, WDR function	
 <p>SE-NP136IR 1.3 megapixel, 1/3"CMOS image sensor, dual-core 32-bit DSP(TI Davinci DM365); Main Stream: 960P@25fps, 720P@25fps SE-NP206IR 2 megapixel, 1/2.5"CMOS image sensor,dual-core 32-bit DSP (TI Davinci DM368); Main Stream: 1080P@25fps ◆IR Distance :120M ◆Adopt 32-bit DSP (TI Vinci Dm368)processing chip with H.264 ◆Support dual coding, AVI format ◆Support code 0.1M~6Mbps and adjustable ◆Auto flip with vertical 180° in omni-directions, no fade zone ◆200 preset positions ◆4 patrol tracking routes ◆4 Pattern scan routes ◆1 auto level scan routes ◆3 class lightning defend</p>	 <p>SE-NP136B 1.3 megapixel, 1/3"CMOS image sensor, dual-core 32-bit DSP(TI Davinci DM365); Main Stream: 960P@25fps, 720P@25fps SE-NP206B 2 megapixel, 1/2.5"CMOS image sensor,dual-core 32-bit DSP (TI Davinci DM368); Main Stream: 1080P@25fps ◆Adopt 32-bit DSP (TI Vinci DM368)processing chip with H.264 ◆Support dual coding, AVI format ◆Support code 0.1M~6Mbps and adjustable ◆Auto flip with vertical 180° in omni-directions, no fade zone ◆200 preset positions ◆4 patrol tracking routes ◆4 Pattern scan routes ◆1 auto level scan routes ◆3 class lightning defend</p>	



SE-NR8104D
4-CH Network Video Recorder
 ◆Video in:1080P*2CH, 720P*2CH;or 960P*4CH
 ◆Video out:1CH BNC,1CH VGA and 1CH HDMI Output
 ◆4CH Audio in and 1CH Audio Output
 ◆Display Resolution: 1080P(1920×1080)/720P(1280×720)
 ◆Recording Resolution: 30fps@1080P(1920×1080)/30fps@720P(1280×720)
 ◆Playback: 4CH playback at the same time, 1080P/720P
 ◆Privacy Zone: Support 4 Privacy zones each channel
 ◆Network interface: RJ45 10M/100M
 ◆Backup mode:HDD/USB device/network
 ◆Support 1 SATA ports,up to 4TB
 ◆Support wireless interface: 3G & WIFI
 ◆Support 2 USB 2.0 Interface
 ◆Support iPhone,Windows Mobile,BlackBerry, Android smart phone,Symbian
Note:8-CH(SE-NR8108D)& 16-CH (SE-NR8116D) is available



SE-NR8104P
4-CH Economic Network Video Recorder
 ◆Video in:1080P*2CH, 720P*2CH;or 960P*4CH
 ◆Video out:1CH BNC,1CH VGA and 1CH HDMI Output
 ◆4CH Audio in and 1CH Audio Output
 ◆Display Resolution: 1080P(1920×1080)/720P(1280×720)
 ◆Recording Resolution: 30fps@1080P(1920×1080)/30fps@720P(1280×720)
 ◆Playback: 4CH playback at the same time, 1080P/720P
 ◆Privacy Zone: Support 4 Privacy zones each channel
 ◆Network interface: RJ45 10M/100M
 ◆Backup mode:HDD/USB device/network
 ◆Support 1 SATA ports,up to 4TB
 ◆Support wireless interface: 3G & WIFI
 ◆Support 3 USB 2.0 Interface
 ◆Support iPhone,Windows Mobile,BlackBerry, Android smart phone,Symbian
Note:8-CH(SE-NR8108P)is available



SE-NR8216Q
16-CH Network Video Recorder
 ◆Video in:720P*16CH, or 960P*16CH,or 1080P*16CH
 ◆Video out:1CH BNC,1CH VGA and 1CH HDMI Output
 ◆16CH Audio in and 1CH Audio Output
 ◆4CH Alarm in and 2CH Output
 ◆Display Resolution: 1080P(1920×1080)/960P(1280×960)/720P(1280×720)
 ◆Recording Resolution: 30fps@1080P(1920×1080)/30fps@960P(1280×960)/30fps@720P(1280×720)
 ◆4 channel 1080P cameras realtime live view
 ◆Playback: 4CH playback at the same time, 1080P/720P
 ◆Privacy Zone: Support 4 Privacy zones each channel
 ◆Network interface: RJ45 10M/100M/1000M
 ◆Backup mode:HDD/USB device/network
 ◆Support 2 SATA ports, up to 8TB
 ◆Support wireless interface: 3G & WIFI
 ◆Support RS485 interface/2 USB 2.0 Interface
 ◆Support iPhone,Windows Mobile,BlackBerry, Android smart phone,Symbian
Note:4-CH(SE-NR8204Q)& 9-CH (SE-NR8209Q) is available



SE-NR8236S
36-CH Network Video Recorder
 ◆Video in:36CH 960P/720P Full Screen or 25CH 1080P or 8CH 3M or 4CH 5M
 ◆Video out:1CH BNC,1CH VGA and 1CH HDMI Output
 ◆36CH Audio in and 1CH Audio Output
 ◆16CH Alarm in and 4CH Output
 ◆Display Resolution: 1080P(1920×1080)/960P(1280×960)/720P(1280×720)
 ◆Recording Resolution: 30fps@1080P(1920×1080)/30fps@960P(1280×960)/30fps@720P(1280×720)
 ◆Playback: Any 4ch 1080P/960/720P playback simultaneously
 ◆Privacy Zone: Support 4 Privacy zones each channel
 ◆Network interface: RJ45 10M/100M/1000M
 ◆Backup mode:HDD/USB device/network
 ◆Support 9 SATA ports+1 E-SATA ports
 ◆Support wireless interface: 3G & WIFI
 ◆Support RS485 interface/3 USB 2.0 Interface
 ◆Support iPhone,Windows Mobile,BlackBerry, Android smart phone,Symbian
Note:9-CH(SE-NR8209S)& 20-CH (SE-NR8220S) is available



SE-CA164T 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS
SE-CA184T 1/3" Sony CCD 800TVL,Optimal WDR, OSD 3D/2D-NR(HDNR),HLC
SE-CA464T 1/3" Sony 1.3 Megapixel Sensor,720P, 3D NR, Digital Zoom, OSD IR Distance:30-50M
 Led: 42MILx2pcs Array IR Led
 Lens: MTV Lens 6/3.6/8/12mm



SE-CA343X 1/4" HD Digital Sensor 700TVL
SE-CA353X 1/3" HD Digital Sensor 800TVL
SE-CA143X 1/3" Sony CCD 500TVL
SE-CA153X 1/3" Sony CCD 650TVL,DWDR,DNR
SE-CA163X 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS
 IR Distance:20-30M
 Led: 42MILx1pc Array IR Led
 Lens: CS Lens 6/4/8/12mm



SE-CA166T 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS
SE-CA186T 1/3" Sony CCD 800TVL,Optimal WDR, OSD 3D/2D-NR(HDNR),HLC
SE-CA466T 1/3" Sony 1.3 Megapixel Sensor,720P, 3D NR, Digital Zoom, OSD IR Distance:50-70M
 Led: 42MILx3pcs Array IR Led
 Lens: CS Lens 8/6/12/16mm



SE-CA346X 1/4" HD Digital Sensor 700TVL
SE-CA356X 1/3" HD Digital Sensor 800TVL
SE-CA146X 1/3" Sony CCD 500TVL
SE-CA156X 1/3" Sony CCD 650TVL,DWDR,DNR
SE-CA166X 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS
SE-CA186X 1/3" Sony CCD 800TVL,Optimal WDR, OSD 3D/2D-NR(HDNR),HLC
 IR Distance:30-50M
 Led: 42MILx2pcs Array IR Led
 Lens: CS Lens 8/6/12/16mm




SE-CA168T 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS
SE-CA188T 1/3" Sony CCD 800TVL,Optimal WDR, OSD 3D/2D-NR(HDNR),HLC
SE-CA468T 1/3" Sony 1.3 Megapixel Sensor,720P, 3D NR, Digital Zoom, OSD IR Distance:80-100M
 Led: 42MILx4pcs Array IR Led
 Lens: CS Lens 12/8/16mm



SE-CA348X 1/4" HD Digital Sensor 700TVL
SE-CA358X 1/3" HD Digital Sensor 800TVL
SE-CA148X 1/3" Sony CCD 500TVL
SE-CA158X 1/3" Sony CCD 650TVL,DWDR,DNR
SE-CA168X 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS
SE-CA188X 1/3" Sony CCD 800TVL,Optimal WDR, OSD 3D/2D-NR(HDNR),HLC
 IR Distance:80-100M
 Led: 42MILx4pcs Array IR Led
 Lens: CS Lens 12/8/16mm

 <p>SE-CA344V 1/4" HD Digital Sensor 700TVL SE-CA354V 1/3" HD Digital Sensor 800TVL SE-CA144V 1/3" Sony CCD 500TVL SE-CA154V 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA164V 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS SE-CA184V 1/3" Sony CCD 800TVL, Optimal WDR, OSD, 3D/2D-NR(HDNR), HLC SE-CA464V 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD IR Distance: 30-40M Led: 42MILx2pcs Array IR Led Lens: MTV Lens 6/3.6/8/12mm</p>	 <p>SE-CA346Y 1/4" HD Digital Sensor 700TVL SE-CA356Y 1/3" HD Digital Sensor 800TVL SE-CA146Y 1/3" Sony CCD 500TVL SE-CA156Y 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA166Y 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS SE-CA186Y 1/3" Sony CCD 800TVL, Optimal WDR, OSD, 3D/2D-NR(HDNR), HLC SE-CA466Y 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD IR Distance: 50-70M Led: 42MILx3pcs Array IR Led Lens: CS Lens 8/6/12/16mm</p>
 <p>SE-CA344J 1/4" HD Digital Sensor 700TVL SE-CA354J 1/3" HD Digital Sensor 800TVL SE-CA144J 1/3" Sony CCD 500TVL SE-CA154J 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA164J 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS IR Distance: 40-60M Led: 28MILx3pcs Array IR Led Lens: 2.8-12mm Manual Zoom Lens</p>	 <p>SE-CA346J 1/4" HD Digital Sensor 700TVL SE-CA356J 1/3" HD Digital Sensor 800TVL SE-CA146J 1/3" Sony CCD 500TVL SE-CA156J 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA166J 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS IR Distance: 60-80M Led: 28MILx4pcs Array IR Led Lens: 2.8-12mm Manual Zoom Lens</p>
 <p>SE-CA344M 1/4" HD Digital Sensor 700TVL SE-CA354M 1/3" HD Digital Sensor 800TVL SE-CA144M 1/3" Sony CCD 500TVL SE-CA154M 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA164M 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS SE-CA184M 1/3" Sony CCD 800TVL, Optimal WDR, OSD, 3D/2D-NR(HDNR), HLC SE-CA464M 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD IR Distance: 40-60M Led: 28MILx3pcs Array IR Led Lens: 2.8-12mm Manual Zoom Lens</p>	 <p>SE-CA346M 1/4" HD Digital Sensor 700TVL SE-CA356M 1/3" HD Digital Sensor 800TVL SE-CA146M 1/3" Sony CCD 500TVL SE-CA156M 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA166M 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS SE-CA186M 1/3" Sony CCD 800TVL, Optimal WDR, OSD, 3D/2D-NR(HDNR), HLC SE-CA466M 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD IR Distance: 60-80M Led: 28MILx4pcs Array IR Led Lens: 2.8-12mm Manual Zoom Lens</p>

 <p>SE-CA346R 1/4" HD Digital Sensor 700TVL SE-CA356R 1/3" HD Digital Sensor 800TVL SE-CA146R 1/3" Sony CCD 500TVL SE-CA156R 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA166R 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS IR Distance: 40-60M Led: 42MILx1pc Array IR Led Lens: CS Lens 8/6/4/12mm</p>	 <p>SE-CA348R 1/4" HD Digital Sensor 700TVL SE-CA358R 1/3" HD Digital Sensor 800TVL SE-CA148R 1/3" Sony CCD 500TVL SE-CA158R 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA168R 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS IR Distance: 60-80M Led: 42MILx2pcs Array IR Led Lens: CS Lens 12/8/6/16mm</p>
 <p>SE-CA356W 1/3" HD Digital Sensor 800TVL SE-CA146W 1/3" Sony CCD 500TVL SE-CA156W 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA166W 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS SE-CA186W 1/3" Sony CCD, 800TVL, Optimal WDR, OSD, 3D/2D-NR(HDNR), HLC SE-CA466W 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD IR Distance: 40-60M Led: 42MILx2pcs Array IR Led Lens: CS Lens 8/6/12mm</p>	 <p>SE-CA342G 1/4" HD Digital Sensor 700TVL SE-CA352G 1/3" HD Digital Sensor 800TVL SE-CA142G 1/3" Sony CCD 500TVL SE-CA152G 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA162G 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS SE-CA462G 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD IR Distance: 25-30M Led: 28MILx2pcs Array IR Led Lens: MTV Lens 3.6/6/8mm</p>
 <p>SE-CA344G 1/4" HD Digital Sensor 700TVL SE-CA354G 1/3" HD Digital Sensor 800TVL SE-CA144G 1/3" Sony CCD 500TVL SE-CA154G 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA164G 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS SE-CA184G 1/3" Sony CCD 800TVL, Optimal WDR, OSD, 3D/2D-NR(HDNR), HLC SE-CA464G 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD IR Distance: 30-40M Led: 28MILx3pcs Array IR Led Lens: MTV Lens 4/6/8mm</p>	 <p>SE-CA344GT 1/4" HD Digital Sensor 700TVL SE-CA354GT 1/3" HD Digital Sensor 800TVL SE-CA144GT 1/3" Sony CCD 500TVL SE-CA154GT 1/3" Sony CCD 650TVL, DWDR, DNR SE-CA164GT 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS SE-CA184GT 1/3" Sony CCD, 800TVL, Optimal WDR, OSD, 3D/2D-NR(HDNR), HLC SE-CA464GT 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD IR Distance: 30-40M Led: 28MILx3pcs Array IR Led Lens: 2.8-12mm Manual Zoom Lens</p>

Array IR Led Day&Night Camera

SecuEasy



SE-CA342P 1/4" HD Digital Sensor 700TVL
SE-CA352P 1/3" HD Digital Sensor 800TVL
SE-CA142P 1/3" Sony CCD 500TVL
SE-CA152P 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CA162P 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance: 25-30M
 Led: 28MILx2pcs Array IR Led
 Lens: MTV Lens 3.6/6/8mm



SE-CA142C 1/3" Sony CCD 500TVL
SE-CA152C 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CA162C 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
SE-CA182C 1/3" Sony CCD 800TVL, Optimal WDR, OSD, 3D/2D-NR(HDNR), HLC
 IR Distance: 25-30M
 Led: 42MILx1pc Array IR Led
 Lens: MTV Lens 3.6/6mm



SE-CA356U 1/3" HD Digital Sensor 800TVL
SE-CA166U 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
SE-CA176U 1/3" Sony Effio-P CCD 700TVL, Real WDR, ATR-EX, OSD, 3D-NR, DIS, HLC, Slow shutter(Sens-up), E-zoom
 IR Distance : 40-60M
 Led: 42MILx2pcs Array IR Led
 Lens: CS Lens 8/6/12/16/4mm
 2.8-12mm Vari-focal lens optional
 Water resistance: IP67
 Temperature: -40°C~+70°C



SE-CA358U 1/3" HD Digital Sensor 800TVL
SE-CA168U 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
SE-CA178U 1/3" Sony Effio-P CCD 700TVL, Real WDR, ATR-EX, OSD, 3D-NR, DIS, HLC, Slow shutter(Sens-up), E-zoom
 IR Distance : 60-80M
 Led: 42MILx3pcs Array IR Led
 Lens: CS Lens 16/6/8/12mm
 2.8-12/9-22mm Vari-focal lens optional
 Water resistance: IP67
 Temperature: -40°C~+70°C



SE-CI352HF 1/3" HD Digital Sensor 800TVL
 IR Distance: 20-30M
 Led: 5*36pcs
 Lens: MTV Lens 4/6/8mm



SE-CD352HE 1/3" HD Digital Sensor 800TVL
 IR Distance: 10-15M
 Led: 8*10pcs
 Lens: MTV Lens 4/6mm

IR Led Day&Night Camera

SecuEasy



SE-CI344J 1/4" HD Digital Sensor 700TVL
SE-CI354J 1/3" HD Digital Sensor 800TVL
SE-CI144J 1/3" Sony CCD 500TVL
SE-CI154J 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CI164J 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance: 40M
 Led: 5*42pcs
 Lens: 2.8-12mm Manual Zoom Lens
 Size: 200x171x83mm



SE-CI346J 1/4" HD Digital Sensor 700TVL
SE-CI356J 1/3" HD Digital Sensor 800TVL
SE-CI146J 1/3" Sony CCD 500TVL
SE-CI156J 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CI166J 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance: 60M
 Led: 5*72pcs
 Lens: 2.8-12mm Manual Zoom Lens
 9-22mm Vari-focal lens optional
 Size: 240x186x100mm



SE-CI344M 1/4" HD Digital Sensor 700TVL
SE-CI354M 1/3" HD Digital Sensor 800TVL
SE-CI144M 1/3" Sony CCD 500TVL
SE-CI154M 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CI164M 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
SE-CI184M 1/3" Sony CCD, 800 TVL, Optimal WDR, OSD 3D/2D-NR(HDNR), HLC
SE-CI466M 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD
 IR Distance: 40M
 Led: 5*42pcs
 Lens: 2.8-12mm Manual Zoom Lens
 Size: 260x112x85mm



SE-CI346M 1/4" HD Digital Sensor 700TVL
SE-CI356M 1/3" HD Digital Sensor 800TVL
SE-CI146M 1/3" Sony CCD 500TVL
SE-CI156M 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CI166M 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
SE-CI186M 1/3" Sony CCD, 800 TVL, Optimal WDR, OSD 3D/2D-NR(HDNR), HLC
SE-CI466M 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD
 IR Distance: 60M
 Led: 5*72pcs
 Lens: 2.8-12mm Manual Zoom Lens
 9-22mm Vari-focal lens optional
 Size: 275x125x105mm



SE-CI144I 1/3" Sony CCD 500TVL
SE-CI154I 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CI164I 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance : 40M
 Led: 8*36pcs
 Lens: 2.8-12mm Manual Zoom Lens
 Size: 240x186x100mm



SE-CI144H 1/3" Sony CCD 500TVL
SE-CI154H 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CI164H 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance : 40M
 Led: 8*36pcs
 Lens: 2.8-12mm Manual Zoom Lens
 Size: 155x97x97mm

 <p>SE-CI343NT 1/4" HD Digital Sensor 700TVL SE-CI353NT 1/3" HD Digital Sensor 800TVL SE-CI143NT 1/3" Sony CCD 500TVL SE-CI153NT 1/3" Sony CCD 650TVL,DWDR,DNR SE-CI163NT 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS IR Distance :30-40M Led: \varnothing 5*42pcs Lens:2.8-12mm Manual Zoom Lens Size:139x78x70mm</p>	 <p>SE-CI344NT 1/4" HD Digital Sensor 700TVL SE-CI354NT 1/3" HD Digital Sensor 800TVL SE-CI144NT 1/3" Sony CCD 500TVL SE-CI154NT 1/3" Sony CCD 650TVL,DWDR,DNR SE-CI164NT 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS IR Distance :40M Led: \varnothing 8*36pcs Lens:2.8-12mm Manual Zoom Lens Size:163x99x85mm</p>
 <p>SE-CI344N 1/4" HD Digital Sensor 700TVL SE-CI354N 1/3" HD Digital Sensor 800TVL SE-CI144N 1/3" Sony CCD 500TVL SE-CI154N 1/3" Sony CCD 650TVL,DWDR,DNR SE-CI164N 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS IR Distance :50M Led: \varnothing 8*36pcs Lens:CS Lens12/6/8/16mm Size:155x85x98mm</p>	 <p>SE-CI342N 1/4" HD Digital Sensor 700TVL SE-CI352N 1/3" HD Digital Sensor 800TVL SE-CI142N 1/3" Sony CCD 500TVL SE-CI152N 1/3" Sony CCD 650TVL,DWDR, DNR SE-CI162N 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS IR Distance :20M Led: \varnothing 5*24pcs Lens:MTV Lens 3.6/6/8mm</p>
 <p>SE-CI343P 1/4" HD Digital Sensor 700TVL SE-CI353P 1/3" HD Digital Sensor 800TVL SE-CI143P 1/3" Sony CCD 500TVL SE-CI153P 1/3" Sony CCD 650TVL,DWDR,DNR SE-CI163P 1/3" Sony Effio-E CCD 700TVL, ATR, OSD,2D-NR,HLC,CRS IR Distance:30M Led: \varnothing 5*48pcs Lens:MTV Lens 6/3.6/8mm Size: 150x80x79mm</p>	 <p>SE-CI344P 1/4" HD Digital Sensor 700TVL SE-CI354P 1/3" HD Digital Sensor 800TVL SE-CI144P 1/3" Sony CCD 500TVL SE-CI154P 1/3" Sony CCD 650TVL,DWDR,DNR SE-CI164P 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS IR Distance:50M Led: \varnothing 8*36pcs Lens:CS Lens 12/6/8/16mm Size: 200x105x99mm</p>

 <p>SE-CI341H 1/4" HD Digital Sensor 700TVL (IR Cut Filter optional) SE-CI351H 1/3" HD Digital Sensor 800TVL SE-CI141H 1/3" Sony CCD 500TVL SE-CI161H 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS IR Distance :10-15M Led: \varnothing 5*24pcs Lens:MTV Lens 3.6/6mm Size:110x65x59mm</p>	 <p>SE-CI342V 1/4" HD Digital Sensor 700TVL SE-CI352V 1/3" HD Digital Sensor 800TVL SE-CI142V 1/3" Sony CCD 500TVL SE-CI152V 1/3" Sony CCD 650TVL, DWDR,DNR SE-CI162V 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS SE-CI182V 1/3" Sony CCD 800TVL,Optimal WDR, OSD,3D/2D-NR(HDNR),HLC SE-CI462V 1/3" Sony 1.3Megapixel Sensor,720P, 3D NR, Digital Zoom, OSD IR Distance:20-30M Led: \varnothing 5*30pcs Lens:MTV Lens 6/3.6/8/12mm</p>
 <p>SE-CI341J 1/4" HD Digital Sensor 700TVL SE-CI351J 1/3" HD Digital Sensor 800TVL SE-CI141J 1/3" Sony CCD 500TVL IR Distance: 10M Led: \varnothing 5*24pcs Lens: MTV Lens 3.6/6mm Size:100x70x59mm</p>	 <p>SE-CI342J 1/4" HD Digital Sensor 700TVL SE-CI352J 1/3" HD Digital Sensor 800TVL SE-CI142J 1/3" Sony CCD 500TVL SE-CI152J 1/3" Sony CCD 650TVL, DWDR, DNR SE-CI162J 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS IR Distance :20-25M Led: \varnothing 5*24pcs Lens: MTV Lens 6/3.6/8mm Size:100x70x69mm</p>
 <p>SE-CI342C 1/4" HD Digital Sensor 700TVL SE-CI352C 1/3" HD Digital Sensor 800TVL SE-CI142C 1/3" Sony CCD 500TVL SE-CI152C 1/3" Sony CCD 650TVL,DWDR,DNR SE-CI162C 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS IR Distance: 20M Led: \varnothing 5*24pcs Lens: MTV Lens 3.6/6/8mm</p>	 <p>SE-CI342D 1/4" HD Digital Sensor 700TVL (IR Cut Filter optional) SE-CI352D 1/3" HD Digital Sensor 800TVL SE-CI142D 1/3" Sony CCD 500TVL SE-CI152D 1/3" Sony CCD 650TVL,DWDR,DNR IR Distance :20M Led: \varnothing 5*24pcs Lens:MTV Lens 6/3.6/8mm Size:125x75x68mm</p>

IR Led Day&Night Camera

SecuEasy



SE-CI342G 1/4" HD Digital Sensor 700TVL
SE-CI352G 1/3" HD Digital Sensor 800TVL
SE-CI142G 1/3" Sony CCD 500TVL
SE-CI152G 1/3" Sony CCD 650TVL,DWDR,DNR
SE-CI162G 1/3" Sony Effio-E CCD 700TVL,ATR,
 OSD,2D-NR,HLC,CRS
 IR Distance:20M
 Led: \varnothing 5*36pcs
 Lens:MTV Lens 6/3.6/8mm
 Size: 120x75x68mm



SE-CI118B 1/4" Sony CCD, 420TVL
 30times Optical zoom
 (3.9mm-117mm vari-focal lens)
SE-CI118BS 1/4" Sony CCD, 540TVL
 35times Optical zoom
 (3.9mm-136.5 mm vari-focal lens)
 IR distance: 100-120m
 Lens: Panasonic Lens Automatic focus
 Voltage: AC 220V
 Constant Temperature outdoor with fan



SE-CD340A 1/4" HD Digital Sensor 700TVL
SE-CD140A 1/3" Sony CCD 500TVL
SE-CD150A 1/3" Sony CCD 650TVL,DWDR,DNR
 Lens:MTV Lens 3.6/6/8mm



SE-CD340B 1/4" HD Digital Sensor 700TVL
SE-CD140B 1/3" Sony CCD 500TVL
SE-CD150B 1/3" Sony CCD 650TVL,DWDR,DNR
 Lens:MTV Lens 3.6/6/8mm
 2.8mm Lens optional



SE-CD340D 1/4" HD Digital Sensor 700TVL
SE-CD140D 1/3" Sony CCD 500TVL
SE-CD150D 1/3" Sony CCD 650TVL, DWDR,DNR
SE-CD160D 1/3" Sony Effio-E CCD 700TVL,ATR,
 OSD,2D-NR,HLC,CRS
 Lens: MTV Lens 3.6/6/8mm



SE-CD340E 1/4" HD Digital Sensor 700TVL
SE-CD160E 1/3" Sony Effio-E CCD 700TVL,ATR,
 OSD,2D-NR,HLC,CRS
 Lens:MTV Lens 3.6/6/8mm
 2.8mm Lens optional

Color Dome Camera

SecuEasy



SE-CD340G 1/4" HD Digital Sensor 700TVL
SE-CD140G 1/3" Sony CCD 500TVL
SE-CD150G 1/3" Sony CCD 650TVL,DWDR,DNR
SE-CD160G 1/3" Sony Effio-E CCD 700TVL,ATR,
 OSD,2D-NR,HLC,CRS
 Lens: 2.8-12mm Manual Zoom Lens



SE-CD342G 1/4" HD Digital Sensor 700TVL
SE-CD142G 1/3" Sony CCD 500TVL
SE-CD152G 1/3" Sony CCD 650TVL,DWDR,DNR
SE-CD162G 1/3" Sony Effio-E CCD 700TVL,ATR,
 OSD,2D-NR,HLC,CRS
 IR Distance:20M
 Led: \varnothing 5*21pcs
 Lens: 2.8-12mm Manual Zoom Lens
 (4-9mm Auto Iris lens or 3.6mm fixed
 lens optional)



SE-CD342C 1/4" HD Digital Sensor 700TVL
SE-CD352C 1/3" HD Digital Sensor 800TVL
SE-CD142C 1/3" Sony CCD 500TVL
SE-CD152C 1/3" Sony CCD 650TVL, DWDR,DNR
 IR Distance: 20M
 Led: \varnothing 5*24pcs
 Lens: MTV Lens 6/3.6/8mm
White color optional



SE-CD342I 1/4" HD Digital Sensor 700TVL
SE-CD352I 1/3" HD Digital Sensor 800TVL
SE-CD142I 1/3" Sony CCD 500TVL
SE-CD152I 1/3" Sony CCD 650TVL,DWDR,DNR
 IR Distance: 25M
 Led: \varnothing 5*24pcs
 Lens: MTV Lens 3.6/6/8mm
Black color optional



SE-CV342F 1/4" HD Digital Sensor 700TVL
SE-CV352F 1/3" HD Digital Sensor 800TVL
SE-CV142F 1/3" Sony CCD 500TVL
SE-CV152F 1/3" Sony CCD 650TVL,DWDR,DNR
SE-CV162F 1/3" Sony Effio-E CCD 700TVL,ATR,
 OSD,2D-NR,HLC,CRS
 IR Distance: 20M
 Led: \varnothing 5*24pcs
 Lens: MTV Lens 6/3.6/8mm



SE-CV342H 1/4" HD Digital Sensor 700TVL
SE-CV352H 1/3" HD Digital Sensor 800TVL
SE-CV142H 1/3" Sony CCD 500TVL
SE-CV152H 1/3" Sony CCD 650TVL,DWDR,DNR
SE-CV162H 1/3" Sony Effio-E CCD 700TVL,ATR,
 OSD,2D-NR,HLC,CRS
 IR Distance: 20M
 Led: \varnothing 5*24pcs
 Lens: MTV Lens 3.6/6/8mm

Vandal-proof Dome Camera

SecuEasy



SE-CV342KA 1/4" HD Digital Sensor 700TVL
SE-CV352KA 1/3" HD Digital Sensor 800TVL
SE-CV142KA 1/3" Sony CCD 500TVL
SE-CV152KA 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV162KA 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance: 20M
 Led: \varnothing 5*24pcs
 Lens: MTV Lens 3.6/6/8mm



SE-CV342K 1/4" HD Digital Sensor 700TVL
SE-CV352K 1/3" HD Digital Sensor 800TVL
SE-CV142K 1/3" Sony CCD 500TVL
SE-CV152K 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV162K 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance: 20M
 Led: \varnothing 5*24pcs
 Lens: MTV Lens 3.6/6/8mm



SE-CV342D 1/4" HD Digital Sensor 700TVL
SE-CV352D 1/3" HD Digital Sensor 800TVL
SE-CV142D 1/3" Sony CCD 500TVL
SE-CV162D 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance: 20M
 Led: \varnothing 5*24pcs
 Lens: MTV Lens 3.6mm lens



SE-CV342E 1/4" HD Digital Sensor 700TVL
SE-CV142E 1/3" Sony CCD 500TVL
SE-CV152E 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV162E 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance: 20M
 Led: \varnothing 5*30pcs
 Lens: CS Lens 6/4/8mm



SE-CV340D 1/4" HD Digital Sensor 700TVL
SE-CV140D 1/3" Sony CCD 500TVL
SE-CV150D 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV160D 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 Lens: MTV Lens 3.6/6/8mm



SE-CV340C 1/4" HD Digital Sensor 700TVL
SE-CV140C 1/3" Sony CCD 500TVL
SE-CV150C 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV160C 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 Lens: 2.8-12mm manual Iris Lens

Vandal-proof Dome Camera

SecuEasy



SE-CV140E 1/3" Sony CCD 500TVL
SE-CV150E 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV160E 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 Lens: MTV Lens 3.6/6/8mm



SE-CV140B 1/3" Sony CCD 500TVL
SE-CV150B 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV160B 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
SE-CV180B 1/3" Sony CCD 800TVL, Optimal WDR, OSD, 3D/2D-NR(HDNR), HLC
 Lens: 2.8-12mm manual Iris Lens



SE-CV143H 1/3" Sony CCD 500TVL
SE-CV153H 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV163H 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance: 30M
 Led: \varnothing 5*36pcs
 Lens: 2.8-12mm Manual Zoom Lens



SE-CV353F 1/4" HD Digital Sensor 700TVL
SE-CV143F 1/3" Sony CCD 500TVL
SE-CV153F 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV163F 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
 IR Distance: 30M
 Led: \varnothing 5*36pcs
 Lens: 2.8-12mm Manual Zoom Lens



SE-CV142B 1/3" Sony CCD 500TVL
SE-CV152B 1/3" Sony CCD 650TVL, DWDR, DNR
 Lens: 2.8-12mm Manual Zoom Lens
SE-CV162B 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
SE-CV182B 1/3" Sony CCD 800TVL, Optimal WDR, OSD 3D/2D-NR(HDNR), HLC
SE-CV462B 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD
 IR Distance: 20M
 Led: \varnothing 5*30pcs
 Lens: 2.8-12mm Vari-focal, Auto Iris Lens



SE-CV142C 1/3" Sony CCD 500TVL
SE-CV152C 1/3" Sony CCD 650TVL, DWDR, DNR
SE-CV162C 1/3" Sony Effio-E CCD 700TVL, ATR, OSD, 2D-NR, HLC, CRS
SE-CV182C 1/3" Sony CCD 800TVL, Optimal WDR, OSD 3D/2D-NR(HDNR), HLC
SE-CV462C 1/3" Sony 1.3 Megapixel Sensor, 720P, 3D NR, Digital Zoom, OSD
 IR Distance: 20M
 LED: \varnothing 5*22pcs
 Lens: 2.8-12mm Manual Zoom Lens

Box Camera



 <p>SE-CB150A 1/3" Sony CCD 650TVL,DWDR,DNR, OSD Menu SE-CB160A 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS SE-CB180A 1/3" Sony CCD,800TVL,Optimal WDR, OSD,3D/2D-NR(HDNR),HLC</p>	 <p>SE-CB140B 1/3" Sony CCD 500TVL SE-CB150B 1/3" Sony CCD 650TVL,DWDR,DNR, OSD Menu SE-CB160B 1/3" Sony Effio-E CCD 700TVL, OSD,ATR ,HLC,CRS (Super Digital Noise Reduction)</p>
 <p>SE-CB340D 1/4" HD Digital Sensor 700TVL SE-CB140D 1/3" Sony CCD 500TVL With Audio</p>	 <p>SE-CB130C Color 1/3" Sony CCD 420TVL</p>
 <p>SE-CB160F 1/3" Sony Effio-E CCD 700TVL, 0.0003Lux Wide Dynamic Range With 3D-DNR OSD Menu 8X Digital Zoom WDR/BLC/ECLPS HLC,8 Zone Motion Detection Privacy Region Shielded</p>	 <p>SE-CZ110A Color Intergrative Camera 1/4" Sony CCD 420TVL 30times Optics Automatic focus</p>

Special Camera



 <p>SE-CD110GW 1/4" Sony CCD 420TVL Lens: 1.6 mm 130°Super Wide Angle No distortion</p>	 <p>SE-CV341D 1/4" HD Digital Sensor 700TVL SE-CV351D 1/3" HD Digital Sensor 800TVL SE-CV141D 1/3" Sony CCD 500TVL SE-CV161D 1/3" Sony Effio-E CCD 700TVL, ATR, OSD,2D-NR,HLC,CRS IR Distance:10M Led: \varnothing 5*12pcs Lens: Board Lens 3.6mm Size: \varnothing 59x55(H)mm</p>
 <p>SE-SP140P 1/3" Sony CCD 500TVL Lens: 3.7mm Pinhole Lens</p>	 <p>SE-SP340M 1/4" HD Digital Sensor 700TVL SE-SP140M 1/3" Sony CCD 500TVL SE-SP150M 1/3" Sony CCD 650TVL,DWDR, DNR,OSD Menu (Optional) SE-CA160M 1/3" Sony Effio-E CCD 700TVL,ATR, OSD,2D-NR,HLC,CRS Lens: MTV Lens 3.6/6/8mm</p>
 <p>SE-CM140S 1/3" Sony CCD 500TVL Lens:3.7mm Taper Pinhole Lens</p>	 <p>SE-CM130B 1/3" Sony CCD 420TVL Lens: 3.7mm Taper Pinhole Lens</p>



SE-CP416A(Outdoor)



SE-CP416B(Outdoor)



SE-CP416CI(Indoor)

6 Inch High Speed Dome Camera**Specifications:**

- ◆Hard and soft setting address design
- ◆With power-off memory function
- ◆Continuously rotate 360 degrees
- ◆200 preset positions,6 programmable preset tours
- ◆Speed adjustable,horizontal / vertical max speed 280°/s
- ◆Integration kinds of protocol, baud rate optional
- ◆RS485 Interface: speed dome addresses from 1~255
- ◆Built-in multi-functional video OSD,easy operation.
- ◆Convenient to setup protocol, ID address and baud rate via key board
- ◆Wide voltage: DC 12V-AC 24V
- ◆Weather-proof design, protection grade is IP66



SE-CP416IR

6 Inch High Speed Dome IR Camera**Specifications:**

- ◆IR distance: 80-100 meters
- ◆With power-off memory function
- ◆Continuously rotate 360 degrees, 128 preset positions.
- ◆6 programmable preset tours
- ◆Speed adjustable,horizontal / Vertical max speed 280°/s
- ◆RS485 Interface: speed dome addresses from 1~255
- ◆Built-in multi-functional video OSD, easy operation.
- ◆Weather-proof design, protection Grade is IP66
- ◆**Camera Specification:**
SECUEASY SE-CZ110B:1/4" SONY Super HAD CCD, 480TVL, 27X optical zoom, 0.01Lux, Day/Night.



SE-CP414IR

3.5" Inch High Speed Dome IR Camera**Specifications:**

- ◆Night vision IR distance 25m
- ◆Continuously rotate 360 degrees
- ◆200 preset positions
- ◆Speed adjustable,the horizontal max speed 360°/s
- ◆4 channels alarm input, 1 channel alarm, output OSD menu,pelco-D/P
- ◆8 programmable preset tours
- ◆Remote control RS485 Interface:1-255
- ◆**Camera Specification:**
SAMSUNG SDM-100P 1/4 CCD,Day 540 TVL; Night 570 TVL,0.7LUX(Day)/0.002LUX(Night), 10 Times optical auto focus
Optional Camera: 10X, 1/4" SONY Super HAD CCD, 10X(f=3.8~38mm), Color 480TVL



SE-CP414A

3.5 Inch High Speed Dome Camera**Specifications:**

- ◆Continuously rotate 360 degrees, 128 preset positions.
- ◆Speed adjustable,horizontal / Vertical max speed 360°/s
- ◆4 channels alarm input,1 channel alarm output, OSD menu,pelco-D/P
- ◆8 programmable preset tours
- ◆Remote control RS485 Interface:1-255
- ◆**Camera Specification:**
SAMSUNG SDM-100P 1/4 CCD, Day 540TVL; Night 570TVL, 0.7 LUX(Day)/0.002LUX (Night), 10 Times optical auto focus.
Optional Camera Specification: 10X, 1/4" SONY Super HAD CCD, 10X (f=3.8~38mm), Color 480TVL



SE-CP434ER

4" Indoor High Speed Dome Camera**Specifications:**

- ◆With power-off memory function
- ◆Pan range: 0°~360°Continue,Tilt range: 0°~180°Flip
- ◆Pan Speed: Max 80°/sec
- ◆200 preset positions
- ◆4 patrol tracking routes, every can insert 24 spots
- ◆4 Pattern scan routes, each can record 100 consecutive moves
- ◆4 auto level scan routes with left & right spacing, speed can be set
- ◆RS485, Pelco D/P supported
- ◆**Camera Specification:**
1/4" SONY Super HAD CCD, 10X(f=3.8~38mm), Color 650TVL



SE-CP420C

Integrated High-Speed Pan Tilt Camera**Specifications:**

- ◆With power-off memory function
- ◆Continuously rotate 360 degrees
- ◆128 preset positions
- ◆Alterable auto tour speed 1°~40°/sec
- ◆Preset target: 150°/sec for pan, 80°/sec for tilt
- ◆Manual control: pan: 0.1°~100° /sec, tilt: 0.1°~80° /sec
- ◆Integration Kinds of protocol, baud rate could transfer freedom optional
- ◆8 programmable preset tours
- ◆RS-485 feed back the pan&tilt
- ◆Built-in multi-functional video OSD,easy operation



SE-CP420P

Integrated High-Speed Pan Tilt Camera**Specifications:**

- ◆With IR LEDs, IR distance: 100 meters
- ◆With power-off memory function
- ◆Continuously rotate 360 degrees
- ◆128 preset positions
- ◆Alterable auto tour speed 1°~40°/sec
- ◆Preset target: 150°/sec for pan, 80°/sec for tilt
- ◆Manual control: pan: 0.1°~100° /sec, tilt: 0.1°~80° /sec
- ◆Integration Kinds of protocol, baud rate could transfer freedom optional
- ◆8 programmable preset tours
- ◆RS-485 feed back the pan&tilt
- ◆Built-in multi-functional video OSD,easy operation

SECUEASY	SE-CZ110A	1/4" Sony CCD 420TVL 1.0Lux (color)/ 0.1Lux (black), can be 0 Lux when it have IR lamp. 27times Optical zoom f=3.3~89.0mm Automatic focus, DC12V
SECUEASY	SE-CZ110B	1/4" Sony CCD 480TVL 1.0Lux (color)/ 0.1Lux (black), can be 0 Lux when it have IR lamp. 27times Optical zoom f=3.3~89.0mm Automatic focus, DC12V
SECUEASY	SE-CZ110C	1/4" Sony CCD 650TVL 1.0Lux (color)/ 0.01Lux (black), can be 0 Lux when it have IR lamp. 27times Optical zoom f=3.3~89.0mm Automatic focus, DC12V
CNB	21Z22	22*10X Color to B/W, 1/4" Sony super HAD CCD, 480TVL, 44 million pixels, build-in 22X optical zoom/10X digital zoom, f=3.6~79.2mm.
SAMSUNG	SCM-2231	23 * 10X, Color to B/W, 1/4" interline Transfer CCD, 44 million pixels, 540TVL/0.7 LUX (color), 570TVL/0.1Lux (B/W), Samsung SSNR noise reduction chip, exercise monitoring functions, build-in 23X optical zoom / 10X digital zoom f=3.84-88.4mm
SONY	FCB-EX45CP	1/4" Sony CCD, 480TVL, 0.1Lux, 18x optical.
SONY	FCB-EX480CP	1/4" Sony CCD, 480TVL, 0.01Lux, 18x optical, Day/night.
SONY	FCB-EX1020P	1/4" Sony Exview HAD CCD, 550TVL, 0.01Lux, 36x optical, Day/night, f=3.4-122.4mm.



SE-PC400S

(3 axis and 2.5 inch TFT LCD with high resolution)

Speed Dome Controller, Metal Shell

1. Special study code function, can amend order by itself
2. Set different protocol and baud rate by RS485
3. Renovate system function on line. Upgrade software and hardware in time
4. Inquiry protocol and baud rate of preset control address by one-dial
5. Button set different parameter, easy to operate
6. Can connect 15pcs sub-keyboard at most



SE-PC400D

(3 axis)



SE-PC400C

(2 axis)



SE-PC400T

(2.5 inch LCD)

1. Portable tester with video input
2. Auto identity NTSC/PAL
3. Power-saving mode can display in a standby state
4. Small appearance, highly integrated and practical
5. Audio test function
6. Support DC12V output, charging for camera.
7. Built-in rechargeable battery, Automatic charging function
8. Particularly suitable for project installation of the camera effects, the lens range, the lens view angle, etc. adjust positioning, save time and effort, convenience



SE-PC400T3

(3.5 inch TFT display)

SE-RM6245

4-CH H.264 Mobile Surveillance DVR with 15" LCD

- ◆ Built-in 15" LCD Monitor
- ◆ 4CH video in and 1CH video out
- ◆ 4CH audio in and 1CH audio out
- ◆ Realtime Recording
- Recording Frame: PAL: 25f/s/ch
NTSC: 30f/s/ch (Quad)



- ◆ Recording resolution:
NTSC: 120fps@CIF; 120fps@halfD1; 60fps@D1
PAL: 100fps@CIF; 100fps@halfD1; 50ps@D1
 - ◆ USB mouse/remote/PTZ control/alarm
 - ◆ Continuous, Motion detection, Sensor activated, Time Schedule
 - ◆ Network: 1 RJ-45 10/100Mbps Ethernet connector
 - ◆ Support 1×2TB SATA HDD
 - ◆ Strong network function, Auto ID function
 - ◆ 3G Mobile phone WAP surveillance
 - ◆ CMS is available
 - ◆ English, Spanish, Portuguese, Russian etc menu
- Note: 8-CH (SE-RM6285) is available**

SE-RM6289

8-CH H.264 Mobile Surveillance DVR with 18.5" LCD

- ◆ Built-in 18.5" LCD Monitor
- ◆ 8CH video in and 1CH video out
- ◆ 8CH audio in and 1CH audio out
- ◆ Realtime Recording
- Recording Frame: PAL: 25f/s/ch
NTSC: 30f/s/ch (Quad)



- ◆ Recording resolution:
NTSC: 240fps@CIF; 120fps@halfD1; 60fps@D1
PAL: 200fps@CIF; 100fps@halfD1; 50ps@D1
 - ◆ USB mouse/remote/PTZ control/alarm
 - ◆ Continuous, Motion detection, Sensor activated, Time Schedule
 - ◆ Network: 1 RJ-45 10/100Mbps Ethernet connector
 - ◆ Support 2×2TB SATA HDD
 - ◆ Strong network function, Auto ID function
 - ◆ 3G Mobile phone WAP surveillance
 - ◆ CMS is available
 - ◆ English, Spanish, Portuguese, Russian etc menu
- Note: 16-CH (SE-RM6269) is available**



SE-RD614H
4-CH Economic H.264 Mobile Surveillance Network DVR

- ◆ 4CH video in and 1CH video out
- ◆ 1CH audio in and 1CH audio out
- ◆ Recording resolution:
 NTSC:120fps@CIF;
 PAL:100fps@CIF
- ◆ Support 1×2TB SATA HDD
- ◆ Strong network function
- ◆ Mobile phone WAP surveillance
- ◆ With VGA connector
- ◆ CMS is available
- ◆ English, Spanish, Portuguese, Russian etc menu

Note :8-CH(SE-RD618H)is available



SE-RD614
4-CH Economic H.264 Mobile Surveillance Network DVR

- ◆ 4CH video in and 1CH video out
- ◆ Recording resolution:
 NTSC:120fps@CIF;60fps@halfD1;30fps@D1
 PAL:100fps@CIF;50fps@halfD1;25fps@D1
- ◆ Support 1×2TB SATA HDD
- ◆ Strong network function,Auto ID function
- ◆ Mobile phone WAP surveillance
- ◆ With VGA connector
- ◆ CMS is available
- ◆ English, Spanish, Portuguese, Russian etc menu

Note :8-CH(SE-RD618)is available



SE-RD624V
4-CH H.264 Mobile Surveillance Network DVR

- ◆ 4CH video in and 1CH video out
- ◆ 4CH audio in and 1CH audio out
- ◆ Recording resolution:
 NTSC:120fps@CIF;120fps@halfD1;60fps@D1
 PAL:100fps@CIF;100fps@halfD1;50fps@D1
- ◆ USB mouse/remote/PTZ control/alarm
- ◆ Support 1×2TB SATA HDD
- ◆ Strong network function,Auto ID function
- ◆ Mobile phone WAP surveillance
- ◆ With VGA connector
- ◆ CMS is available
- ◆ English, Spanish, Portuguese, Russian etc menu

Note:8-CH (SE-RD628V) is available



SE-RD634D
4-CH H.264 Mobile Surveillance Network DVR with HDMI

- ◆ 4CH video in and 3CH video out
- ◆ 4CH audio in and 1CH audio out
- ◆ Recording resolution:
 NTSC:120fps@CIF,120fps@halfD1,100fps@D1
 PAL:100fps@CIF,100fps@halfD1,80fps@D1
- ◆ USB mouse/remote/ PTZ control
- ◆ Support 2 SATA Interface
- ◆ Strong network function,no need apply DDNS
- ◆ Mobile phone WAP surveillance
- ◆ HDMI/BNC/VGA Output
- ◆ English, Spanish, Portuguese, Russian etc menu

Note :8-CH(SE-RD638D)is available, support 960H



SE-RD616H
16-CH H.264 Mobile Surveillance Network DVR

- ◆ 16CH video in and 1CH video out
- ◆ 4CH audio in and 1CH audio out
- ◆ Display resolution:
 PAL: D1(704*480) . NTSC: D1(704*576)
- ◆ Recording resolution:
 PAL: 400fps@CIF , NTSC: 480fps@CIF
- ◆ Support mouse/remote/PTZ control
- ◆ Support 1×2TB HDD
- ◆ Support Remote Client, IE Brower, Mobile, Firefox, Google Chrome
- ◆ Mobile phone WAP surveillance
- ◆ With VGA Output
- ◆ CMS is available
- ◆ English, Spanish, Portuguese,Russian etc menu



SE-RD626B
16-CH H.264 Mobile Surveillance Network DVR with HDMI

- ◆ 16CH video in and 1CH video out
- ◆ 16CH audio in and 1CH audio out
- ◆ Recording resolution:
 NTSC: 480fps@ CIF;240fps@halfD1;120fps@D1
 PAL: 400fps@ CIF, 200fps@halfD1, 100fps@D1
- ◆ USB mouse/remote/PTZ control/alarm
- ◆ Support 2×2TB SATA HDD
- ◆ Strong network function,Auto ID function
- ◆ Mobile phone WAP surveillance
- ◆ With VGA and HDMI Output
- ◆ CMS is available
- ◆ DVD-RW is optional
- ◆ English, Spanish, Portuguese,Russian etc menu



SE-RD738
8-CH H.264 full D1 real-time Playback Mobile Surveillance Network DVR with HDMI

- ◆ 8CH video in and 3CH video out
- ◆ 8CH audio in and 1CH audio out
- ◆ Recording resolution:
 NTSC:200fps@D1
 PAL:160fps@D1
- ◆ Pentaplex,4 channel playback simultaneously
- ◆ Support network remote, USB backup
- ◆ Support 2x 2TB SATA HDD
- ◆ Mobile phone WAP surveillance
- ◆ HDMI/BNC/VGA Output
- ◆ Support DVD-RW
- ◆ English, Spanish,Portuguese,Russian etc menu

Note:16-CH (SE-RD736) is available



SE-RD722
32-CH H.264 Mobile Surveillance Network DVR with HDMI

- ◆ 32CH video in and 1CH video out
- ◆ 16CH audio in and 1CH audio out
- ◆ Recording resolution:
 NTSC:960fps@CIF;
 PAL:800fps@CIF
- ◆ Support 4CH D1,28CH CIF real time
- ◆ USB mouse/remote/USB backup/PTZ control
- ◆ Support 4x 2TB SATA HDD
- ◆ Mobile phone WAP surveillance
- ◆ HDMI/BNC/VGA Output
- ◆ WIFI function optional
- ◆ English, Spanish,Portuguese,Russian etc menu

Note:24-CH (SE-RD724)is available

<p>19"22" LED Monitor</p>		<p>19"26"32"42"46" LCD Monitor</p>	
<p>SE-AB508 Bracket</p>	<p>SE-AB509 Bracket</p>	<p>SE-AB513 Bracket</p>	<p>SE-AB506 Bracket</p>
<p>SE-AH405 Outdoor housing Size:320mm*115mm*115mm</p>	<p>SE-AH406 Outdoor housing with bracket Size:360mm*115mm*125mm</p>	<p>SE-AH406S Outdoor housing Size:260mm*115mm*125mm</p>	<p>SE-AH407 Indoor housing Size:300mm*100mm*119mm</p>
<p>Power Supply</p>	<p>Power Supply</p>	<p>Power Supply</p>	<p>Power Box</p>

<p>BNC</p>	<p>Power Connector</p>	<p>CCTV Extension Cable BNC(M) to RCA(M)</p>	<p>DC Wire Adapter</p>
<p>DC Wire Adapter DC(F) to Row and DC(M)</p>	<p>DC Wire Adapter DC(F) to DC(M) and Pin</p>	<p>DC Wire Adapter DC(F) to 4DC(M) DC(F) to 10DC(M)</p>	<p>DC Wire Adapter DC(F) to 16DC(M)</p>
<p>CCTV Extension Cable Option:Length=10/20/30/50M</p>	<p>Aluminum Foil Shield Cable Option:Length=10/20/30/50M</p>	<p>CCTV Extension Cable Option:Length=75/100/200M</p>	<p>CCTV Extension cable RG59+Power Length:200M</p>
<p>SE-UTP102T/R UTP Video Balun Transfer Distance≤2400M (1800M color signal)</p>	<p>SE-UTP101P UTP Video Balun Transfer Distance≤350M (color signal)</p>	<p>SE-UTP101B Video Balun with Video, Audio & Power Transfer Distance≤350M (color signal)</p>	<p>SE-UTP101VP SE-UTP101PVD Video Balun with Video, Audio,Power&Data Transfer Distance≤350M (color signal)</p>

 <p>SE-UTP104P</p>	 <p>SE-UTP108P</p>	 <p>SE-UTP104AR</p>	 <p>SE-UTP108AR</p>
 <p>LED Illuminator</p>	 <p>LED Illuminator</p>	 <p>Microphone</p>	 <p>Microphone</p>
 <p>Auto Iris Lens</p>	 <p>Fixed Lens</p>	 <p>Motorized zoom lens</p>	 <p>RS232-485 converter</p>
 <p>Indoor Decoder</p>	 <p>Outdoor Universal Pan/tilt with built-in decoder board</p>	 <p>Indoor horizontal Pan/Tilt Plastic, with built-in decoder board</p>	 <p>SE-AP301C Pan/Tilt Controller</p>